

# Product data sheet

Specifications



## Rack PDU, Basic, Zero U, 15A, 100/120V, (14) 5-15

AP9567

### Overview

**Presentation** APC Basic Rack PDUs distribute reliable rack power distribution via a single input with multiple output receptacles. Easily mount this vertical PDU in racks or enclosures. It occupies zero U of valuable rack space, which allows space for more equipment in the rack. This vertical PDU does not require additional tools to mount into APC NetShelter Enclosures. Enables a quick recovery from overload events. Packaging Includes PDU, Installation guide, Rack Mounting brackets, Toolless Mounting Kit.

**Lead time** Usually in Stock

### Main

**Color** Black

**Product or Component Type** PDU

**PDU Type** Basic

**Cord length** 12 ft (3.7 m)

**Number of cables** 1

**Provided Equipment** Installation guide  
Rack Mounting brackets  
Toolless Mounting Kit

### Complementary

**Input Voltage** 100 V  
120 V

**Height** 24.02 in (61 cm)

**Width** 1.73 in (4.4 cm)

**Output Voltage** 100 V  
120 V

**Depth** 1.73 in (4.4 cm)

**Product Weight** 4.81 lb(US) (2.18 kg)

**Mounting Location** Side

**Mounting preference** No preference

**Input Plug Type** NEMA 5-15P

**Mounting Mode** Rack-mounted

**Rack units** 0U

**Mounting position** Vertical

**Line Rated Current** 12 A

**Acceptable Input Voltage** 100...125 V

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

|                                 |               |
|---------------------------------|---------------|
| <b>Input current limits</b>     | 15 A          |
| <b>Load Capacity</b>            | 1400 VA       |
| <b>Input Frequency</b>          | 50/60 Hz      |
| <b>Outlet type and quantity</b> | 14 NEMA 5-15R |

## Environment

|  |  |
|--|--|
| <b>Product Certifications</b>                | cUL Listed<br>METI Denan<br>UL Listed            |
| <b>Ambient air temperature for operation</b> | 32...113 °F (0...45 °C)                          |
| <b>Relative Humidity</b>                     | 0...95 %   |
| <b>Operating altitude</b>                    | 0...10000 ft                                     |
| <b>Ambient Air Temperature for Storage</b>   | -13...149 °F (-25...65 °C)                       |
| <b>Storage Relative Humidity</b>             | 0...95 %   |
| <b>Storage altitude</b>                      | 0...50000 ft (0.0000000000...15240.0000000000 m) |

## Ordering and shipping details

|             |              |
|-------------|--------------|
| <b>GTIN</b> | 731304207061 |
|-------------|--------------|

## Packing Units

|                                     |                       |
|-------------------------------------|-----------------------|
| <b>Unit Type of Package 1</b>       | PCE                   |
| <b>Number of Units in Package 1</b> | 1                     |
| <b>Package 1 Height</b>             | 25.51 in (64.8 cm)    |
| <b>Package 1 Width</b>              | 5.98 in (15.2 cm)     |
| <b>Package 1 Length</b>             | 7.01 in (17.8 cm)     |
| <b>Package 1 Weight</b>             | 6.44 lb(US) (2.92 kg) |

## Contractual warranty

|                 |                           |
|-----------------|---------------------------|
| <b>Warranty</b> | 2 years repair or replace |
|-----------------|---------------------------|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) 55

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant

REACH Regulation [REACH Declaration](#)

California proposition 65 **WARNING:** This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

Halogen content performance Product contains halogen above thresholds

### Energy efficiency

Optimized Energy Efficiency Energy efficient product

## Use Again

### Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back Yes

Image of product / Alternate images

Alternative

---



