Product data sheet

Specifications



APC Smart-UPS Modular Ultra 20kW Frame, N+1 Redundant, Rackmount, 208/120V

SRYLF20KRMT

Overview

Lead time	Usually in Stock

Main

Main Input Voltage	208 V AC
Product or Component Type	Frame
Main Output Voltage	120 V AC
Kw Rating	20000 W
Rated power in VA	20000 VA
Battery Type	Li-Ion (Lithium Ion)
Range of Product	Smart-UPS Modular Ultra Accessories

General

product web sub-family	Network management card
Number of power module	2
Number preinstalled power module	2

Physical

color	Silver
Height	20.5 in (520 mm)
Width	17.3 in (440 mm)
Depth	29.1 in (740 mm)
Product Weight	130.3 lb(US) (59.1 kg)

Input

Input Frequency	40 - 70 Hz
Number of input connectors	1 Hard Wire 4-wire (2PH+N+G)
Maximum Input Current per Phase	51 A
Load power factor	0.5 leading to 0.5 lagging

Output

Topology	On-Line
Waveform Type	Sine wave

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Overload Operation	60 seconds @ 125% and 30 seconds @ 150%
Bypass type	Built-in Bypass

Ordering and shipping details

GTIN	731304420156

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.81 in (30 cm)
Package 1 Width	23.62 in (60 cm)
Package 1 Length	39.37 in (100 cm)
Package 1 Weight	60.08 lb(US) (27.25 kg)

Contractual warranty

Warranty	5 Years

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	5ee38369-4dfb-4636-ab65-b08aa3242891
REACh Regulation	REACh Declaration

Use Again

Repack and remanufacture

Circularity Profile	End of Life Information
Take-back	No

Image of product / Alternate images

Alternative

