

Product data sheet

Specifications



3-Pole Circuit Breaker, 150A, T3 Type for Symmetra PX250/500kW

PD3P150AT3B

Overview

Lead time Special Order - Call for Quoted Lead Times

Main

Main Input Voltage	480 V 3 phase 400 V 3 phase
Main Output Voltage	480 V 3 phase 400 V 3 phase
Output connector type	Hard Wire 3-wire (3P) 1
Provided Equipment	Installation guide

Physical

Height	17.008 in (43.2 cm)
Width	22.008 in (55.9 cm)
Depth	21.5 in (54.6 cm)
Net Weight	6.22 lb(US) (2.82 kg)
mounting location	Front
Mounting preference	No preference
Mounting Mode	Not rack-mountable

Input

Max line current	150 A
Input Frequency	50 Hz 60 Hz

Output

Maximum Total Current Draw per Phase	150 A
--------------------------------------	-------

Conformance

Product Certifications	CE UL Listed
------------------------	-----------------

Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Ambient Air Temperature for Storage	5...104 °F (-15...40 °C)

Ordering and shipping details

GTIN 731304267188

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	17.008 in (43.2 cm)
Package 1 Width	21.5 in (54.6 cm)
Package 1 Length	22.008 in (55.9 cm)
Package 1 Weight	8.2 lb(US) (3.7 kg)

Contractual warranty

Warranty 1 year repair or replace

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)

Eu Rohs Directive

Under investigation
