



Product: [10GXM13](#)

10GXM (0.230") Category 6A Cable, 4 Pair, U/UTP, CMP

Product Description

10GXM (0.230" Diameter) Category 6A Premise Horizontal Cable (500MHz), 4 Pair, 23 AWG Solid Bare Copper Conductors, U/UTP, Plenum-CMP, Flamarrest® PVC-LS Jacket

Technical Specifications

Product Overview

Suitable Applications:	Premise Horizontal Cable, Ethernet 10GBASE-T, Wi-Fi 6, Wi-Fi 5, In-Building Wireless, In-Building Small Cells, Mobile RAN, PoE++, PoE+, PoE, HDBaseT
------------------------	--

Construction Details

Conductor

Size	Stranding	Material	No. of Pairs
23 AWG	Solid	BC - Bare Copper	4

Insulation

Material	Color Code
FEP - Fluorinated Ethylene Propylene	White & Blue, White & Orange, White & Green, White & Brown

Outer Jacket

Material	Material Trade Name	Nom. Diameter	Ripcord
PVC - Polyvinyl Chloride	Flamarrest®	0.230	Yes

Outer Jacket1 Table Notes:	Core wrapped with EquiBlock™ Barrier Technology
Overall Cable Diameter (Nominal):	0.230

Electrical Characteristics

Electricals

Max. Conductor DCR	Max. Capacitance Unbalance	Nom. Characteristic Impedance
93.8 Ohm/km (28.6 Ohm/1000ft)	330 pF/100m	100 Ohm

Delay

Max. Delay	Max. Delay Skew	Nom. Velocity of Prop.
537.6 ns/100m	45 ns/100m	69%

High Frequency

Frequency [MHz]	Max. Insertion Loss (Attenuation) [dB/100m]	Min. NEXT [dB]	Min. PSNEXT [dB]	Min. ACR [dB]	Min. PSACR [dB]	Min. ACRF (ELFEXT) [dB]	Min. PSACRF (PSELFEXT) [dB]	Min. RL (Return Loss) [dB]	Max./Min. Input Impedance (unFitted) [Ohm]	Max./Min. Fitted Impedance [Ohm]	Min. PSANEXT [dB]	Min. PSAACRF [dB]	Min. TCL [dB]	Min. ELTCTL [dB]
1	2.1	74.3	72.3	72.2	70.2	67.8	64.8	20.0	100 ± 15	105 ± 10	67.0	67.0	40.0	35.0
4	3.8	65.3	63.3	61.5	59.5	55.8	52.8	23.0	100 ± 15	105 ± 10	67.0	66.2	40.0	23.0
8	5.3	60.8	58.8	55.4	53.4	49.7	46.7	24.5	100 ± 15	105 ± 10	67.0	60.1	40.0	16.9
10	5.9	59.3	57.3	53.4	51.4	47.8	44.8	25.0	100 ± 15	105 ± 10	67.0	58.2	40.0	15.0
16	7.5	56.2	54.2	48.8	46.8	43.7	40.7	25.0	100 ± 15	105 ± 10	67.0	54.1	38.0	10.9
20	8.4	54.8	52.8	46.4	44.4	41.8	38.8	25.0	100 ± 15	105 ± 10	67.0	52.2	37.0	9.0
25	9.4	53.3	51.3	44.0	42.0	39.8	36.8	24.3	100 ± 15	105 ± 10	67.0	50.2	36.0	7.0

31.25	10.5	51.9	49.9	41.4	39.4	37.9	34.9	23.6	100 ± 15	105 ± 10	67.0	48.3	35.1	5.1
62.5	15.0	47.4	45.4	32.4	30.4	31.9	28.9	21.5	100 ± 15	105 ± 10	65.6	42.3	32.0	
100	19.1	44.3	42.3	25.2	23.2	27.8	24.8	20.1	100 ± 15	105 ± 10	62.5	38.2	30.0	
200	27.6	39.8	37.8	12.2	10.2	21.8	18.8	18.0	100 ± 22	100 ± 10	58.0	32.2	27.0	
250	31.1	38.3	36.3	7.3	5.3	19.8	16.8	17.3	100 ± 32	100 ± 10	56.5	30.2	26.0	
300	34.3	37.1	35.1	2.9	0.9	18.3	15.3	16.8	100 ± 32	100 ± 10	55.3	28.7	25.2	
350	37.2	36.1	34.1			16.9	13.9	16.3	100 ± 32	100 ± 10	54.3	27.3	24.6	
400	40.1	35.3	33.3			15.8	12.8	15.9	100 ± 32	100 ± 10	53.5	26.2	24.0	
450	42.7	34.5	32.5			14.7	11.7	15.5	100 ± 32	100 ± 10	52.7	25.1	23.5	
500	45.3	33.8	31.8			13.8	10.8	15.2	100 ± 32	100 ± 10	52.0	24.2	23.0	

Voltage

UL Voltage Rating
300 V (CMP)

Mechanical Characteristics

Temperature

UL Temperature	Operating	Storage
105°C	-20°C To +75°C	-20°C To +75°C

Table Notes:	25 lbs
--------------	--------

Bend Radius

Flexing Min.
1 in (25 mm)

Standards and Compliance

Environmental Suitability:	Indoor
Flammability / Reaction to Fire:	NFPA 262, UL 910 (Plenum), FT6
NEC / UL Compliance:	Article 800, CMP, CMP-LP (0.7A)
CEC / C(UL) Compliance:	CMP
ICEA Compliance:	S-116-732
IEEE Compliance:	IEEE 802.3bt Type 1, Type 2, Type 3, Type 4
NEMA Compliance:	ANSI/NEMA WC-66
Data Category:	Category 6A
TIA/EIA Compliance:	ANSI/TIA-568.2-D Category 6A
ISO/IEC Compliance:	IEC 11801-1IEC 61156-5
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), REACH, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE), REACH: 2024-06-07
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Other Standard Compliance(s):	c(UL)us Listed

Product Notes

Notes:	Electrical values are expected performance based on cable testing and representative performance within a typical Belden system. Print Includes Descending Footage/Meter Markings from Max. Put-Up Length to 0.
--------	---

History

Update and Revision:	Revision Number: 0.15 Revision Date: 05-30-2025
----------------------	---

Part Numbers

Variants

Item #	Color	Putup Type	Length
10GXM13 0101000	Black	Reel	1,000 ft
10GXM13010A1000	Black	Reel in Box	1,000 ft
10GXM13 D151000	Blue	Reel	1,000 ft
10GXM13D15A1000	Blue	Reel in Box	1,000 ft
10GXM13 0051000	Green	Reel	1,000 ft
10GXM13005A1000	Green	Reel in Box	1,000 ft
10GXM13 0031000	Orange	Reel	1,000 ft
10GXM13003A1000	Orange	Reel in Box	1,000 ft
10GXM13 0091000	White	Reel	1,000 ft

10GXM13009A1000	White	Reel in Box	1,000 ft
10GXM13 0041000	Yellow	Reel	1,000 ft
10GXM13004A1000	Yellow	Reel in Box	1,000 ft

© 2025 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.