Product data sheet

Specifications



APC Smart-UPS, Line Interactive, 1000VA, Lithium-ion, Rack/Tower, 2U, 120V, 6x NEMA 5-15R outlets, SmartConnect Port+Network Card, Short Depth, AVR

SMTL1000RM2UCNC

Overview

Presentation	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Lead time	Usually in Stock

Main

Product or Component Type	Uninterruptible power supply (UPS)

Complementary

Communication port type	SmartConnect Ethernet port
Software package	SmartConnect software for remote power monitoring feature availability varies by terms of use

Batteries & Runtime

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph
Battery Type	Li-Ion (Lithium Ion)
Battery graph comments	This graph is based on actual measured runtime data. All measurements were taken with new, fully charged batteries and a balanced resistive load (PF = 1.0). Actual runtimes may vary from the values of this graph. Actual runtimes are dependent on several variables including battery age, battery charge level, environmental conditions and characteristics of the connected load.
Extendable Run Time	0
Typical recharge time	3 h
Battery design life	8…10 year(s)
Battery Charge Power (Watts)	79 W rated

General

Provided equipment	Rack Mounting brackets Rack Mounting support rails Screw Washer USB cable Ethernet patch cable
product web sub-family	Cloud-enabled monitoring
Redundant	No

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Physical

Number of rack unit	2U
Cable length	8 ft (2.4 m)
color	Black with silver front bezel
Height	3.39 in (8.6 cm)
Width	17.24 in (43.8 cm)
Depth	12.52 in (31.8 cm)
Product Weight	35.9 lb(US) (16.3 kg)
Mounting preference	Lower
Mounting Mode	Rack-mounted
USB compatible	Yes

Input

Main Input Voltage	120 V
Input Connection Type	NEMA 5-15P
Input protection type	Circuit breaker
Efficiency at full load	75...154 V adjustable 82...144 V
Input Frequency	50/60 Hz +/- 3 Hz auto-sensing

Output

Main Output Voltage	120 V
Kw Rating	800 W
Rated power in VA	1000 VA
output connection type	6 NEMA 5-15R
Crest factor	3 : 1
Harmonic distortion	Less than 5%
Maximum configurable power in VA	1000 VA
Max Configurable Power (Watts)	800 W
Transfer Time	6ms typical : 10ms maximum
Topology	Line Interactive
Waveform Type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz sync to mains

Conformance

Product Certifications	NOM
Equipment protection policy	Lifetime : $150000

Environmental

Acoustic level	41 dBA
Online Thermal Dissipation	135 Btu/h
Operating altitude	0...10000 ft

Ambient air temperature for operation	32…104 °F (0…40 °C)
Ambient Air Temperature for Storage	5…113 °F (-15…45 °C)
Storage altitude	0…25000 ft (0.0000000000…7620.0000000000 m)
IP degree of protection	IP20
Relative Humidity	0…95 % non-condensing
Storage Relative Humidity	0…95 % non-condensing

Communications & Management

Audible Alarm	Audible and visible alarms
control panel	Multi-function LCD status and control console
Free slots	1
Pre-Installed SmartSlot™ Cards	Network management card 3 with environmental monitoring
Communication port support	SmartConnect Ethernet port: for cloud monitoring feature availability varies by terms of use
Alarm	Alarm when on battery : distinctive low battery alarm

Surge Protection and Filtering

Surge energy rating	680 J
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m

Ordering and shipping details

GTIN	731304435464
Country of origin	PH

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.02 in (22.9 cm)
Package 1 Width	1.86 in (4.72 cm)
Package 1 Length	22.99 in (58.4 cm)
Package 1 Weight	41.006 lb(US) (18.6 kg)

Contractual warranty

Warranty	5 year repair or replace

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle)	**1278**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
EU RoHS Directive	**Compliant with Exemptions**
REACh Regulation	**REACh Declaration**

Use Again

Repack and remanufacture

Circularity Profile	**End of Life Information**
Removable battery	**User replaceable**
Take-back	**No**

Image of product / Alternate images

Alternative



