Emergency Panic Stations

Model KR-1
Latching Push Button
With Key Reset

Model PBM-1-4
Momentary Push Button
Mounted on a Red Plate

Model PBL-1-L2
Latching Push Button
With Illuminated Button

- Single Gang 430 Stainless Steel Wallplate
- Normally-Open and/or Normally-Closed Contact Pairs
- Contacts Rated 10A @ 35 VDC or 120VAC
- Temperature Range -25°C to +70°C
- Switch Connection via Screw Terminals
- Switch Depth 2” Behind Plate, 2.5” for Illuminated Models
- UL Listed Components
- Weather-Proof to IP65 Standard, KR models to IP40 Standard
- Large 1.5” Diameter Red Mushroom Button
- Custom Plate Marking Available

MODEL	CONTACTS	PLATE	ILLUMINATION (not available on KR Models)	GUARD RING
PBM MOMENTARY OPERATOR **PBL** LATCHING OPERATOR **KR** LATCHING OPERATOR KEY RESET	**1** 1 N/O PAIR and 1 N/C PAIR **2** 2 N/O PAIRS **3** 2 N/C PAIRS **4** 1 N/C PAIR **5** 1 N/O PAIR	**1** 302 STAINLESS **2** WHITE **3** IVORY **4** RED **5** 1.75” STAINLESS **6** 1.75” RED	**L1** 6 VDC **L2** 12 VDC **L3** 24 VDC **L4** 120 VAC	**GR**

PBL- 1- 4- L2- GR

Part Number Example -
Latching push button with one N/O and one N/C contact pair on a red plate, 12VDC illumination and guard ring.

ALARM CONTROLS
ASSA ABLOY

ASSA ABLOY, the global leader
in door opening solutions