Duplex Receptacles

Heavy Duty Industrial Specification Grade
Tamper-Resistant
15A & 20A, 125V



Brass self-grounding clip is permanently staked on for secure and reliable performance


Wide receptacle face shelf provides exceptional support to the wallplate or box cover

Patented tamper-resistant safety shutter mechanism prevents insertion of foreign objects

Body and face made of impact-resistant advanced engineering polymer for extreme durability

"Universal" strap design provides ample support for electrical box installations, and includes multiple "break-off" tabs to eliminate interference with virtually any cover or wall plate

Provides compliance with National Electrical Code Article 406 for tamper-resistant receptacles



Ground terminal clamp allows for both back and side wiring

Oversized brass terminal screw heads provide superior clamping force and electrical conductivity

External wiring clamps allow for back or side wiring, and provide visual verification of termination and a faster, easier installation

Molded in ribs prevent terminal screws from making contact with wall box

Common Applications

- Commercial Buildings
- Transportation Facilities
- Municipal Buildings
- Education Facilities

Ordering Information

Ratings		15 A/ 125 V	20 A/ 125 V
NEMA Config		5-15R	5-20R
Order ID	Brown	T5262	T5362
	Ivory	T5262-I	T5362-I
	White	T5262-W	T5362-W
	Gray	T5262-GY	T5362-GY
	Red	T5262-R	T5362-R
	Blue	T5262-BU	T5362-BU
	Black	T5262-E	T5362-E
	Light Almond	T5262-T	T5362-T


Specifications

Rating	T5262	T5362
AC Horsepower Rating		
At Rated Voltage	½ HP	1 HP
Electrical Specification		
Amperage	15A	20A
NEMA	5-15R	5-20R
Voltage	125V	
Grounding	Self-Grounding*	
Pole	2	
Wire	3	
Dielectric Voltage	Withstands 3000V min	
Temperature Rise	Max 30°C after 250 Cycles Overload at 200% rated current	
Environmental Specifications		
Flammability	UL94 V0	
Operating Temperature	Maximum continuous 75°C, minimum -40°C (w/o impact)	
Material Specifications		
Face	PBT Polyester Blend	
Body	PBT Polyester Blend	
Strap	Steel (Galvanized G60)	
Ground Contact	0.030" Brass	
Mounting Screw	Triple-Drive Plated Steel	
Ground Screw	#8 Hex Head, Triple-Drive Brass	
Line Contacts	0.030" Phosphor Bronze	
Terminal Clamp	Brass	
Terminal Screws	#8 Triple-Drive Brass	
Ground Clip	Brass	
Shutter Mechanism	Acetal	
Mechanical Specifications		
Product ID.	Ratings are permanently marked on the device	
Terminal ID	Brass - Hot, Silver - Neutral, Green - Ground	
Terminal Accommodation	#14 - #10 AWG	
Wire Types	Solid or Stranded	
Termination	Back and Side Wire	
Standards & Certifications		
NEMA	WD 1 & WD 6	
ANSI	C-73	
Certification/Listing	cULus, NOM-ANCE	
Applicable Standards	UL 498, Fed Spec W-C 596, CSA C22.2 NO. 42	
RoHS	RoHS Compliant	
Warranty		
Product Warranty	10 Years	


*Self-grounding when installed in a properly grounded metallic box

Dimensions

Front View



Side View



Visit our Website at:
www.leviton.com/commercial
email: commercial@leviton.com

Q-1100 071917

Leviton Manufacturing Co., Inc.
201 N Service Rd, Melville, NY 11747
Telephone: 1-800-323-8920 • FAX: 1-800-832-9538
Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): 1-800-824-3005

© 2017 Leviton Manufacturing Co., Inc. All rights reserved.

ISO 9001 REGISTERED Quality Manufacturer