



## 1080p 4-Port HDMI Extending Splitter Transmitter

**Splits One Source to Four Outputs; Extends Signal up to 50 m (165 ft.), Single Ethernet Cable per Receiver, Video Bandwidth Amplifier, Black**  
Part No.: [207829](#)

EAN-13: 0766623207829 | UPC: 766623207829

---

Easily connect and extend up to four HDMI displays to a single source.

The Manhattan 1080p 4-Port HDMI Extending Splitter Transmitter provides the option of connecting and extending as many as four HDMI displays to one High-Definition (1080p, HD) or high-definition 3D source at up to 50 m (165 ft.) distances. This powered HDMI Extending Splitter provides a reliable 1080p resolution video and multichannel audio transmission over longer distances than is possible with HDMI cables.

### Flexible Solution for Many A/V Applications

Ideal for trade shows, classrooms, home theater, conference rooms, business office and retail applications, the Manhattan 1080p 4-Port HDMI Extending Splitter Transmitter boosts and extends a 1080p signal up to 50 m (165 ft.) for convenient display or projector placement. Cat6 Ethernet cabling — UTP, SSTP or SFTP (cables not included) — is less expensive and easier to install than HDMI cabling and in-line signal repeaters.

### Best Possible Image Quality

The Manhattan 1080p 4-Port HDMI Extending Splitter Transmitter is HDMI and HDCP 1.4a compliant and delivers a stunningly clean, crisp and vivid picture at up to 1080p resolution on four displays thanks to an integrated video bandwidth amplifier. Additionally, it supports HD-quality 3D video, as well as LPCM, DTS and Dolby TrueHD audio.

## Features:

- Replicates and extends a High-Definition (HD) digital audio/video signal to up to four HD 1080p HDMI Extending Splitter Receivers (207836 ) at distances up to 50 m (165 ft.) using Ethernet cable
- Supports 1080p resolution as well as HD 3D video and Deep Color (24-bits/pixel)
- 1080p resolution, 3D, Deep Color
- Integrated video bandwidth amplifier
- Supports video-amplifier bandwidth of up to 1.65 Gbps (for 1080p)
- Supports LPCM, DTS Digital, DTS-HD Master Audio and Dolby TrueHD audio
- A flexible Audio/Video solution for conference rooms (when sharing ideas and data), digital signage (extending the distances between displays) and other applications
- Works with PlayStation and Xbox game systems, Blu-ray players, set-top boxes, satellite receivers and more
- Fully HDCP compliant
- This transmitting (Tx) unit requires at least one receiving (Rx) unit (207836) but connects up to four
- AC powered with Plug and Play installation; no special setup or remote required
- Plug-and-play installation
- Gold-plated contacts for corrosion-free connections
- Three-year warranty

## Specifications:

### Standards and Certifications

- HDCP 1.4a
- CE
- FCC
- RoHS2

### General

- Source-to-splitter (TX) range: up to 15 m (49 ft.)
- Cat6 cable 1080p at 50 m (165 ft.)
- Cat6 cable 720p at 60 m (200 ft.)
- Cat6 cable 480p at 80 m (264 ft.)
- Receiver (RX)-to-display range: up to 15 m (49 ft.)
- Power: 12 VDC @ 1 A ; AC power adapter, 0.9 m (2.9 ft.)
- LED power/status indicator
- Wallmountable
- Power: 12 VDC

### Connections

For more information on Manhattan products, consult your local dealer or visit [www.manhattan-products.com](http://www.manhattan-products.com).

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

#### Transmitter

- One HDMI female, 19-pin (input)
  - Four Ethernet female, RJ45 (output)
  - One 5 VDC female, power (input)
- Receiver (sold separately)

- One HDMI female, 19-pin (output)
- One Ethernet female, RJ45 (input)
- One 5 VDC female, power (input)

#### Signal Input/Output

- Input video signal: 400 – 600 mV
- Input DDC signal: 5 V p-p (TTL)
- Maximum single-link range: 1.65 Gbps and 1080p resolution
- Output video: HDMI 1.3, HDCP 1.4a
- Frequency: 1.65 Gbps / 165 MHz

#### Video Resolutions

- DTV/HDTV: 480i/480p/576i/576p/720p/1080i/1080p

#### Physical

- LED indicators: power and port connection
- Power adapter: 12 VDC / 1 A; 0.9 m (2.9 ft.)
- Power switch
- Dimensions: 162 x 100 x 25 mm (6.4 x 3.9 x 1 in.)
- Weight: 0.43 kg (0.95 lbs.)
- Housing: metal

#### Operating Environment

- Operation Temperature: 0 – 40°C (32 – 104°F)
- Storage Temperature: -20 – 60°C (-4 – 140°F)
- Humidity (noncondensing): 0 – 96%

#### Package Contents

- 1080p 4-Port HDMI Extending Splitter Transmitter
- Power adapter
- Wallmounting brackets
- Quick Instruction Guide



