

## Sharp LM551

LCD 55" Infrared Touch Display

# Preliminary Datasheet



### Multi-purpose for interactive engagements

For best-in-class touch performance and value, the Sharp LM series commands feature-rich professional capabilities for small meeting spaces and interactive signage applications. An integrated System on Chip (SoC) with Android 14 CTS-compliant Operating System offers the most up to date features and security for seamless out-of-the-box collaboration.

Boosting creativity in group collaboration, the Sharp LM series features intuitive Pen-on-Paper writing, a built-in whiteboard, annotation overlay mode and Windows Ink support. Using the on-board EShare app, content can be wirelessly shared from any personal device to the display without the need for apps or dongles. A single USB-C cable transmits data, video/audio output and power delivery between notebook and display for the simplest and seamless BYOD workflows.

With its 4-sided uniform slim bezel design, the Sharp LM series supports installations in both landscape and portrait as well as tilted desk. Dedicated features including hide side bars, application lock and a built-in web browser make the Sharp LM series the perfect display for budget-driven interactive signage applications.

### Benefits

**Best readability** - high brightness panel ensures content is readable even in well-lit environments and anti-glare coating avoids distracting reflections.

**Pen-On-Paper user experience** - Zero bonded glass and latest infrared touch technology enable highly accurate and responsive writing and drawing with up to 20 touch points.

**Out-of-the-box collaboration** - the integrated Android PC features a powerful home screen launcher offering fast and flexible access to a range of pre-installed applications.

**Highly customizable** - a variety of settings allow the display to be optimised to meet the needs of different applications, from small meeting and huddle rooms to touch signage and wayfinding.

**Safe & Secure** - latest Android 14 SoC provides a secure operating system which, together with extra security features, meets the highest IT security standards.

## Product Information

Product Name	Sharp LM551
Model	PN-LM551
Product Group	LCD 55" Infrared Touch Display
Order Code	60006142

## Display

Panel Technology	VA with Direct LED backlights
Screen Size [inch/cm]	55 / 138.8
Aspect Ratio	16:9
Brightness (without glass) [cd/m <sup>2</sup> ]	500
Contrast Ratio (typ.)	5000:1
Viewing Angle [°]	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Colour Depth [bn]	1.07 (8bit + FRC)
Response Time (typ.) [ms]	8 (grey-to-grey)
Panel Refresh Rate [Hz]	60
Haze Level [%]	25
Supported Orientation	Landscape; Portrait; Tilt (0 to 45°)

## Touch

Touch Technology	Infrared
Number of Touches	Real multi-touch up to 20 touches
Touch Method	Finger; Gloves; Stylus dual pen tip (2.6mm/6.8mm)
Data Interface	USB 2.0 (full speed) HID; USB powered, plug & play
Accuracy [mm]	+/- 1
Windows Ink	yes
Palm Rejection	no
Operating System	Native Multi-Touch: Windows 8.1/10/11, Linux, Android 9.0 or higher, Chrome OS 87 or higher; Single Touch (Default Mouse): Mac OS 10.15/11/12

## Glass

Type	Thermal-tempered, anti-glare coating; Zero Bonding
Bonding Gap [mm]	0.85
Thickness [mm]	3.1
Hardness [H]	9

## Resolution

Native Resolution	3840 x 2160			
Supported Resolutions	1024 x 768; 1280 x 1024; 1280 x 720;	1280 x 960; 1440 x 900; 1680 x 1050;	1920 x 1080; 3840 x 2160; 4096 x 2160;	640 x 480; 720 x 400; 800 x 600

## Synchronisation Rate

Horizontal Frequency [kHz]	31.5 - 135
Vertical Frequency [Hz]	24 - 70

## Connectivity

Input Video Digital	1x USB Type-C (DisplayPort 1.4 Alt mode, HDCP, 65W PD, Touch signal, USB pass through); 3x HDMI (HDCP2.3, CEC, HDMI3-ARC)
Input Control	1 x RS232; LAN 10Base-T/100Base-TX/1000Base-T; remote control wire (3,5mm jack)
Input Data	1 x USB 2.0 (SoC + Wi-Fi Dongle); 1 x USB 3.0 (type-C); 3 x USB 3.0 (Downstream)
Input Touch	1 x USB 3 (Type-B); 1x USB Type-C (shared with video input)
Output Video Digital	HDMI (HDCP2.3; loop through: HDMI, USB Type-C, Android SoC)
Output Audio Analogue	1 x 3,5 mm jack
Input Detect	Custom; First; Last

## Open Modular Intelligence

OPS Slot	Slot Technology: Open pluggable specification (NEC / Intel OPS standard)
----------	--

## Sensors

Ambient Light Sensor	optional via Sensor Module (KT-RC3)
Human Sensor	optional via Sensor Module (KT-RC3)

## Electrical

Power Consumption [W]	145 shipping
Power Savings Mode [W]	< 0.5 (ECO Standby); < 2 (Networked Standby)
Power Management	VESA DPMS
Power Supply	100-240 V AC; 50/60 Hz

## Environmental Conditions

Operating Temperature [°C]	+5 to +35
-------------------------------	-----------

Operating Humidity [%]	20 to 80
------------------------	----------

Storage Humidity [%]	10 to 80
----------------------	----------

Storage Temperature [°C]	-20 to 60
-----------------------------	-----------

## Mechanical

Dimensions (W x H x D) [mm]	Without stand: 1,265 x 736 x 73
--------------------------------	---------------------------------

Weight [kg]	33
-------------	----

Bezel Width [mm]	15
------------------	----

VESA Mounting [mm]	400 x 400 (FDMI); M6
--------------------	----------------------

Packaging Dimensions (W x H x D) [mm]	1,410 x 885 x 185
--	-------------------

Packaging Weight [kg]	40.5
-----------------------	------

Material	Aluminum alloy (front side); metal (back side)
----------	--

## Embedded Computing

System Version	Android 14
----------------	------------

CPU	Arm Cortex A53x4 2 GHz (octo-core); Arm Cortex A73x4 2.3 GHz
-----	--

System Memory	4G RAM
---------------	--------

Internal Storage	32GB ROM
------------------	----------

Android Features	App side loading (Google CTS compliant); Application lock; Hide Android SoC; Hide side bar; Portrait support (apps and OSD)
------------------	---

Built-in Applications	File Manager; Input Select; Office and PDF Viewer - Office Suite; Setting; Web Browser; Whiteboard; Wireless Screen Sharing - E-Share
-----------------------	---

Built-in Tools	Annotation overlay mode
----------------	-------------------------

## Bluetooth

Bluetooth	5.3 compliant: A2DP; AVRCP; GATT; HID
-----------	---------------------------------------

## Wireless LAN

WLAN	IEEE802.11 a/b/g/n/ac/ax compliant; WPA/WPA2/WPA3 Enterprise, WPS2.0, WAPI, Access Point
------	--

## Available Options

Accessories	Feet (ST-43M); Remote control kit (KT-RC3); Soundbar (PN-ZCMS1); Trolley (PD04 Tipster); USB-C cable (USB-C 5M; USB-C 7M); Wall mount (PDW S 32-65 L & P)
-------------	---

OPS Slot

Recommended: OPS Enterprise Pro (100016118)

## Regulatory

Safety and Ergonomics	CE; CISPR Class B; ECAS; EMC Class B; FCC Class B; RCM; RoHS; UKCA; UL/C-UL; VCCI
Pixel Failure Class	ISO 9241-307, Class 1
Resistance to Fire	Metal backcover, plastic material certified acc. to (TBD)

## Green Features

Energy Efficiency	ECOMode; LED backlight
Ecological Standards	EnergyStar 8.0

## Additional Features

Special Characteristics	CEC Support; HDMI ARC; OSD rotation for portrait mode; Powered USB Port (65 W); Scheduler
Audio	Integrated Speakers (10 W + 10 W)
Shipping Content	2 x Passive Stylus; 2x AAA batteries; Blank Sticker; Bracket for Camera; Cable Clamps; Display; Power Cable; Remote Control; Setup Manual; USB cable; Wireless Adapter
Warranty	3 years warranty incl. backlight; optional 4. + 5. year warranty extension <sup>1</sup>
Operating Hours	18/7
External Control	HDMI CEC; Scheduled Timer
Remote Management	NEC NaViSet Administrator 2
Security	Disable HW Buttons; Disable IR Functionality; Disable USB and LAN Ports; IEEE802.1X (Wi-Fi)

<sup>1</sup> please refer to terms and conditions of warranty extensions



CE



RCM



VCCI



FCC Class B



RoHS

This document is © 2025 Sharp NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 06.05.2025