Product data sheet

Specifications



APC Smart-UPS 750VA 120V SHIPBOARD

SMT750X93

Overview

Lead time	Usually in Stock

Main

Product or Component Type	Uninterruptible power supply (UPS)

Batteries & Runtime

Efficiency	View Efficiency Graph
Battery Type	Lead-Acid battery
Extendable Run Time	0
Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	3 h
RBC Quantity	1
Battery life	3…5 year(s)
Battery Charge Power (Watts)	15 W rated

General

Provided equipment	User Manual
Number of power module	0
product web sub-family	TAA compliance
Redundant	No

Physical

Number of cables	1
Height	6.3 in (161 mm)
Width	5.4 in (138 mm)
Depth	14.5 in (369 mm)
Product Weight	27.6 lb(US) (12.5 kg)
Mounting Location	Front
Mounting preference	No preference
Mounting Mode	Not rack-mountable
Two post mountable	0

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

USB compatible	Yes

Input

Main Input Voltage	120 V
Input Connection Type	NEMA 5-15P
Efficiency at full load	82...144 V 120 V
Input Frequency	50/60 Hz +/- 3 Hz

Output

Main Output Voltage	120 V
Kw Rating	500 W
Rated power in VA	750 VA
output connection type	6 NEMA 5-15R
Harmonic distortion	Less than 5%
Maximum configurable power in VA	750 VA
Max Configurable Power (Watts)	500 W
Transfer Time	6ms typical : 10ms maximum
Topology	Line Interactive
Waveform Type	Sine wave
Full load runtime	00:05:00
Half load runtime	00:15:00
Output frequency	50/60 Hz +/- 3 Hz for 60 Hz nominal sync to mains

Conformance

Product Certifications	CSA C22.2 No 107.1
Marking	UL

Environmental

Acoustic level	41 dBA
Online Thermal Dissipation	90 Btu/h
Operating altitude	0...9842.52 ft (0...3000 m)
Ambient air temperature for operation	32…104 °F (0…40 °C)
Ambient Air Temperature for Storage	-4…131 °F (-20…55 °C)
Storage altitude	0.0000000000…49212.6 ft (0…15000 m)
Relative Humidity	0…95 %
Storage Relative Humidity	0…95 %

Communications & Management

Audible Alarm	Alarm on 25 alarm conditions
control panel	LED status display with load and battery bar-graphs and On Line : On Battery : Replace Battery : and Overload Indicators
Free slots	0

Surge Protection and Filtering

Surge energy rating	593 J
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m

Ordering and shipping details

GTIN	731304433637

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.85 in (30.1 cm)
Package 1 Width	19.65 in (49.9 cm)
Package 1 Length	10.94 in (27.8 cm)
Package 1 Weight	30.91 lb(US) (14.02 kg)

Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle)	649
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
SCIP Number	B2b22a56-41f2-497e-9ea6-cf093b3b8bd3
REACh Regulation	REACh Declaration

Use Again

Repack and remanufacture

Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Image of product / Alternate images

Alternative

