Product data sheet
Characteristics

SY125K500DL-PD
APC Symmetra PX 125kW Scalable to 500kW with Maintenance Bypass Left & Distribution



Overview

Presentation	A high-performance, 3-phase, modular, scalable, power protection solution with industry-leading efficiency, capacity, and performance for medium to large data centers and mission critical environments.
Lead time	Usually Ships within 6 Weeks

General

Provided equipment	Assembly service Installation guide Network Management Card Start-Up Service User Manual
Product web sub-family	Symmetra PX 250/500kW
Bypass Voltage Tolerance	+/-10% settable from +/-4/6/8 and 10%
Performance multiplier	0.350208
Number of tare power	940 W
Number of power module free slots	15
Number of power module filled slots	5
Redundant	Yes
Size UPS version	Internetworking Server Telecom
UPS size	L
Value multiplier	0.81

Physical

Color	Black
Depth	42.13 in (107 cm)
Height	78.39 in (199.1 cm)
Mounting preference	No preference
Product Weight	6300.22 lb(US) (2857.73 kg)
Mounting Mode	Not rack-mountable
Two post mountable	0
USB compatible	No
Width	116.14 in (295 cm)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Input

Input Frequency	40 - 70 Hz auto-sensing
Number of input connectors	1 Hard Wire 4-wire (3PH + G) 1 Hard Wire 5-wire (3PH + N + G)
Efficiency at full load	408...552 V 480 V
Other Input Voltages	415 V
Maximum Short Circuit Withstand (Icw)	50 kA
Input Total Harmonic Distortion	Less than 5% for full load
Input protection type	3-pole breaker
Nominal Input Voltage	3 phase 3 phase
Load power factor	0.5 leading to 0.5 lagging
Cos phi	0.99

Output

Kw Rating	125000 W
Max Configurable Power (Watts)	500000 W
Harmonic distortion	Less than 2%
Output Frequency (sync to mains)	50 Hz sync to mains 60 Hz +/- 0.1 % for 60 Hz nominal not synced 50 Hz +/- 0.1 % for 50 Hz nominal not synced 60 Hz sync to mains
Other Output Voltages	380 V 415 V
Crest factor	Unlimited
Topology	Double Conversion Online
Waveform Type	Sine wave
Output connector type	Hard Wire 4-wire (3PH + G) 1 Hard Wire 5-wire (3PH + N + G) 1
Output voltage tolerance	+/-1% static and +/- 5% at 100% load step
Output Voltage THD	< 2% linear load and < 3% non-linear load
Overload Operation	10 minutes @ 125% and 60 seconds @ 150%
Bypass type	Built-in Maintenance Bypass Built-in Static Bypass
Curve equation	Efficiency
Curve fixed loss	0.0082
Curve load maximum	100 %
Curve load minimum	1 %
Curve proportional loss	0.0156
Curve square loss	0.0162
Curve X-axis maximum	100 %
Curve test cond ID	Curve fit of data measured in accordance with the ENERGY STAR Test Method for Uninterruptible Power Supplies. All measurements taken in normal mode(s), at typical environmental conditions, with 480V/60Hz electrical input and balanced resistive load (PF = 1.0) output.
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Efficiency at full load	96 % in battery operation)
Graph display	1
Output voltage	400 V 3 phase 480 V 3 phase
Maximum configurable power in VA	500000 VA

Rated power in VA	125000 VA
Transfer Time	2ms typical

Conformance

Product Certifications	CUL Listed Eurobat General Purpose UL Listed
Standards	CSA C22.2 No.107.3-05 EN/IEC 62040-1-1 EN/IEC 62040-2 EN/IEC 62040-3 OSHPD UL 1778 UL 60950-1

Environmental

Ambient Air Temperature for Operation	32…104 °F (0…40 °C)
Relative Humidity	0…95 %
Operating altitude	0...3333 ft
Ambient Air Temperature for Storage	5…104 °F (-15…40 °C)
Storage Relative Humidity	0…95 %
Storage altitude	0…50000 ft (0.00…15240.00 m)
Acoustic level	54 dBA
Heat dissipation	19427 Btu/h
Show note OP temperature	No
NEMA degree of protection	NEMA 1
IP degree of protection	IP20

Batteries & Runtime

Battery Type	VRLA
Included Battery Modules	8
Battery Slots Empty	0
Typical recharge time	3.5 h
RBC Quantity	6
Liquid Electrolyte Value	0
Overload Operation	10 minutes @ 125% and 60 seconds @ 150%
Battery curve	P
Battery Charge Power (Watts)	11815 W rated
Battery design life	5…8 year(s)
Battery power in VAH	41472 VAh runtime
Battery option	SYBFXR8-8 1 82944 VAh SYBFXR8-8 3 165888 VAh SYBFXR8-8 5 248832 VAh SYBFXR8-8 7 331776 VAh SYBFXR8-8 2 124416 VAh SYBFXR8-8 4 207360 VAh SYBFXR8-8 6 290304 VAh
Extendable Run Time	1

Communications & Management

Free slots	1
Pre-Installed SmartSlot™ Cards	Network management card 2 with environmental monitoring, out of band access and Modbus
Control panel	Touch Screen LCD User Interface
Emergency Power Off (EPO)	Optional

Ordering and shipping details

Package weight(Lbs)	7176.05 lb(US) (3255 kg)

Packing Units

Package 1 Height	84.65 in (215 cm)
Package 1 width	117.72 in (299 cm)
Package 1 Length	50.00 in (127 cm)

Offer Sustainability

EU RoHS Directive	Not compliant
Optimized Energy Efficiency	Energy efficient product

Contractual warranty

Warranty	1 year on-site repair or replace with factory authorized Start-Up