

## DCNM-DE Discussion device with touchscreen

### DICENTIS



DICENTIS incorporates several standardized technologies that have been combined to create an open platform. Complete system solutions can be created by simply integrating compatible products. This makes DICENTIS extremely scalable, enabling it to evolve with the growing needs of meeting and conference facilities. At its heart, the DICENTIS Conference System makes use of the unique IP based OMNEO media networking architecture, developed by Bosch.

The elegantly designed DICENTIS Discussion devices enable participants to speak, register a request to speak, and listen to discussion.

The DICENTIS Discussion with touchscreen has a 4.3 inch touch screen and is completely software upgradable. It has lots of features including independent dual-use for language selection and voting. A simple software setting enables two participants to share a device and listen to proceeding in two different languages. Separate votes can also be cast on a shared device.

The 4.3 inch capacitive touch screen informs participants of the proceedings and increases meeting efficiency by displaying the current speaker and delegates in the request list. Available interpreted languages and voting information can also be displayed.

#### Functions

##### General

- Single-use and chairperson can be configured via the PC configuration software application.
- 4.3 inch capacitive multi-touchscreen for displaying:

- ▶ 4.3 inch capacitive touch screen and built-in NFC reader for fast recognition of participants
- ▶ Configurable as a single participant, dual-use, or chairperson's device
- ▶ Functionality can be conveniently expanded with software modules

- Multiple user interface languages in original characters.
- Speaker list and Request list.
- Speech countdown timer.
- Custom logo.
- Built-in Near Field Communication (NFC) contactless tag reader.
- Additional functionality by use of software licenses only.
  - Identification functionality.
  - Voting.
  - Select language.
  - Dual use.
- Audio mute button.
- Supports star and loop-through connection.

##### Speech intelligibility

- Crystal-clear sound due to a very high signal-to-noise ratio.
- Maximum speech intelligibility is guaranteed.
- The loudspeaker and microphone can be active at the same time to facilitate a face-to-face meeting experience. A feedback suppressor is built in to prevent acoustic feedback.

##### Security

- Encryption ensures that information within the system remains confidential.

##### Microphones

- A socket is provided to connect the pluggable microphones DCNM-HDMIC, DCNM-MICS or DCNM-MICL (to be ordered separately).

### Headphones and loudspeakers

The device has a headphone connection and independent volume control (on both sides of the device), so the speaker can be heard clearly even when there is excessive background noise.

### Controls and Indicators

Top side of device:

- 4.3 inch capacitive display with touchscreen.
- Microphone with a red or green indicator:
  - Red indicates that the microphone is active.
  - Green indicates that a request-to-speak is accepted.
- LED indicators on device showing:
  - Microphone on state – Red.
  - Possible-to-speak – White.
  - Priority – White (Chairperson only).
  - Request-to-speak – Green.

Left and right-hand side of the device:

- Rotary controls for independent headphone volume control.

### Interconnections

- Socket for pluggable microphone.
- Two 3.5 mm (0.14 in) headphone sockets stereo jack type.
- 2x RJ45 compatible connection for system communication and power.
- Hot Plug-and-play.

### Regulatory information

Region	Regulatory compliance/quality marks	
Global	DOC	DECL COC ISO22259 DICENTIS
Europe	CE	DCNM-DE

### Parts included

Quantity	Component
1	DCNM-DE DICENTIS Discussion device with touchscreen

### Technical specifications

#### Electrical

Supply voltage	48 VDC
Power consumption	5 W
Frequency response	100 Hz to 20 kHz (-3 dB at nominal level)
THD at nominal level	< 0.1 %
Dynamic range	> 90 dB

Signal-to-noise ratio	> 90 dB
-----------------------	---------

#### Audio inputs

Nominal microphone input	80 dB SPL according to ISO22259 (IEC60914)
Maximum microphone input	110 dB SPL according to ISO22259 (IEC60914)

#### Audio outputs

Loudspeaker nominal output	72 dB SPL at 0.5 m
Loudspeaker maximum output	87 dB SPL
Headphone nominal output	0 dBV
Headphone maximum output	3 dBV
Headphone load impedance	> 32 ohm < 1k ohm
Headphone output power	65 mW

#### General

Screen size	109.22 mm (4.3 in)
Screen type	Capacitive multi-touch
Supported contactless NFC tag	According to: ISO/IEC14443 Type A (from 106 kbps to 848 kbps. MIFARE 106kbps).

#### Mechanical

Mounting	Tabletop
Dimensions (H x W x D) without microphone	72 x 259 x 139 mm (2.8 x 10.2 x 5.5 in)
Color (top and base)	Traffic black (RAL 9017)
Weight	Approx. 1035 g (2.3 lb)

#### Environmental

Operating temperature	5 °C to +45 °C (41 °F to +113 °F)
Storage and transport temperature	-30 °C to +70 °C (-22 °F to +158 °F)

Relative humidity	< 90 %, > 5%
-------------------	--------------

### Ordering information

#### DCNM-DE Discussion device with touchscreen

DICENTIS Discussion device with 4.3 inch touch screen and NFC identification reader. Choice of pluggable microphone to be ordered separately.

Order number **DCNM-DE | F.01U.400.587 F.01U.313.729**

### Accessories

#### DCNM-HDMIC High directive microphone

DICENTIS High Directive Microphone for the DICENTIS Conference System or DICENTIS Wireless Conference System.

Order number **DCNM-HDMIC | F.01U.374.038 F.01U.269.132**

#### DCNM-MICS Microphone with short stem

DICENTIS short stem microphone for the DICENTIS Conference System or DICENTIS Wireless Conference System.

Order number **DCNM-MICS | F.01U.374.039 F.01U.288.448**

#### DCNM-MICL Microphone with long stem

DICENTIS long stem microphone for the DICENTIS Conference System or DICENTIS Wireless Conference System.

Order number **DCNM-MICL | F.01U.288.447**

#### DCNM-TCD Transport case for 10x DCNM-xD

Transport case for storing and transporting ten DICENTIS discussion devices, ten high-directive microphones, ten short or long stem microphones, and cables.

Order number **DCNM-TCD | F.01U.335.596**

#### DCNM-DICH ID card holder for DCNM-D

ID card holder for the participant to automatically login when the card is parked and logout when it is removed, 25 pieces in one box.

Order number **DCNM-DICH | F.01U.396.439**

#### DCNM-CB02-I System cable assembly 2m

2 m (6.6 feet), system network cable for connecting all DICENTIS devices.

Order number **DCNM-CB02-I | F.01U.332.138**

#### DCNM-CB05-I System cable assembly 5m

5 m (16.0 feet), system network cable for connecting all DICENTIS devices.

Order number **DCNM-CB05-I | F.01U.332.019**

#### DCNM-CB10-I System cable assembly 10m

10 m (33.0 feet), system network cable for connecting all DICENTIS devices.

Order number **DCNM-CB10-I | F.01U.332.020**

#### DCNM-CB25-I System cable assembly 25m

25 m (82.0 feet), system network cable for connecting all DICENTIS devices.

Order number **DCNM-CB25-I | F.01U.332.021**

#### LBB3443/00 Lightweight headphones

Lightweight headphones for high-quality sound reproduction, replaceable ear pads and normal cable.

Order number **LBB3443/00 | F.01U.508.901**

#### LBB3443/10 Lightweight headphones, braided cable

Lightweight headphones for high-quality sound reproduction, replaceable ear pads and durable cable.

Order number **LBB3443/10 | F.01U.009.041**

#### HDP-LWN Lightweight neckband headphones

Lightweight neckband headphones for high-quality sound reproduction, replaceable ear pads.

Order number **HDP-LWN | F.01U.132.714**

#### HDP-ILN Induction loop neckband

Induction loop neckband, lightweight.

Order number **HDP-ILN | F.01U.012.808**

#### ACD-MFC-ISO Card, MIFAREclassic, 1kB, 50pcs

MIFARE Classic ID card with 1 kByte data storage, 2 application areas, one of which can be customized.

Packing information: 50 cards/ each unit

Order number **ACD-MFC-ISO | F.01U.218.378**

#### ACD-EV1-ISO Card, MIFARE EV1, 8kB, 50pcs

Mifare DESFire EV1 ID card with 8 kByte data storage, 2 application areas, one of which can be customized.

Packing information: 50 cards/ each unit

Order number **ACD-EV1-ISO | F.01U.218.412**

### Software Options

#### DCNM-LSSL License for language selector at 1 seat

The DICENTIS Select Language at Seat license enables the language selection feature of the DICENTIS Multimedia and DICENTIS Discussion device with touchscreen. The DICENTIS Discussion device with language selector has the functionality built-in.

Order number **DCNM-LSSL | F.01U.300.534**

#### DCNM-LSVT License for voting at 1 seat

DICENTIS software license for enabling voting at seat in the DICENTIS Multimedia, DICENTIS Discussion device with touchscreen, and DICENTIS wireless Extended. The DICENTIS Discussion device with voting has the functionality built-in.

Order number **DCNM-LSVT | F.01U.300.532**

#### DCNM-LSID License for identification at 1 seat

DICENTIS software license for enabling identification at seat in the DICENTIS Discussion device with voting, DICENTIS Discussion device with language selector, DICENTIS Discussion device with touchscreen, DICENTIS Multimedia device, and DICENTIS wireless Extended.

Order number **DCNM-LSID | F.01U.300.533**

#### DCNM-LSDU License for 2 seats per device

DICENTIS software license for enabling dual-use at seat in the DICENTIS Discussion device, DICENTIS Discussion device with language selector, DICENTIS Discussion device with touchscreen, and DICENTIS wireless devices.

Order number **DCNM-LSDU | F.01U.310.246**

### Services

#### EWE-DCNDTS-IW 12 mths wrty ext disc unit touscreen

12 months warranty extension

Order number **EWE-DCNDTS-IW | F.01U.348.740**

**Represented by:**

**Europe, Middle East, Africa:**

Bosch Security Systems B.V.  
P.O. Box 80002  
5600 JB Eindhoven, The Netherlands  
Phone: + 31 40 2577 284  
[www.boschsecurity.com/xc/en/contact/](http://www.boschsecurity.com/xc/en/contact/)  
[www.boschsecurity.com](http://www.boschsecurity.com)

**Germany:**

Bosch Sicherheitssysteme GmbH  
Robert-Bosch-Ring 5  
85630 Grasbrunn  
Tel.: +49 (0)89 6290 0  
Fax: +49 (0)89 6290 1020  
[de.securitysystems@bosch.com](mailto:de.securitysystems@bosch.com)  
[www.boschsecurity.com](http://www.boschsecurity.com)

**North America:**

Bosch Security Systems, LLC  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 800 289 0096  
Fax: +1 585 223 9180  
[onlinehelp@us.bosch.com](mailto:onlinehelp@us.bosch.com)  
[www.boschsecurity.com](http://www.boschsecurity.com)

**Asia-Pacific:**

Robert Bosch (SEA) Pte Ltd, Security Systems  
11 Bishan Street 21  
Singapore 573943  
Phone: +65 6571 2808  
Fax: +65 6571 2699  
[www.boschsecurity.com/xc/en/contact/](http://www.boschsecurity.com/xc/en/contact/)  
[www.boschsecurity.com](http://www.boschsecurity.com)