REV	DESCRIPTION	DATE	APPROVAL

Patent Pending

FRONT VIEW

Material	Mild Carbon Steel Rare Earth Magnet
Finish	J Hook -Galvanized Yellow Zinc Magnet & Cup -Triple Coat (NiCuNi)

Magnet Vertical Pull Test

Metal Thickness	Weight
1mm (.04 inches)	22 lbs
2mm (.08 inches)	45 lbs.
3mm (.12 inches)	90 lbs.

Magnet Horizontal Pull Test

Metal Thickness	Weight
3mm (.12 inches)	25 lbs.

3/4" J Hook assembled to permanent magnet
Cat. 5e capacity 16, Cat. 6 capacity 10
Cat. 6A (Min. OD 0.300")2, Cat 6A (Max OD 0.354") 2
UL tested load 17 lbs., packaged 100 pcs. per box

Please read before us. Disclaimer: Mag-Daddy neither assumes nor accepts any liability for damages resulting from the handling or use of magnets. With your purchase, the buyer confirms that you have read and understood the following warnings: the buyer agrees that he/she is responsible for all damages and injuries caused by the magnets, which include personal injuries, property damages and magnet damages. The buyer must agree with the terms before purchase. Pull forces we have provided are estimates only, we are not responsible for any inaccuracy of the magnet pull force. Please test the pull force before any usage.
Magnets are very strong. Handling them with care is necessary to prevent personal injuries, property damages and magnet damages. Can be harmful to pacemaker wearers and others with medical implants.

Release Approval:

Release Date:

Customer Approval:

Tolerances:
.X = +/- 0.02in
.XX = +/- 0.01in
.XXX = +/-.005in
Unless Otherwise Specified

Proprietary Rights: All information that is contained within is proprietary. Not for unauthorized use or disclosure.

MAG DADDY
MAGNETIC FASTENERS
magdaddyusa.com

Title: ¾" Basic J Hook with Magnet Side Mounted

Size:	Scale:	Part Number:	Rev:
A	None	JH12MS	JW

Date:

Drawn by RO X

Drawing Number

Sheet 1 of X