

STI G3 MULTIPURPOSE PUSH BUTTON



KEY FEATURES

General Information

- Optional IP camera helps identify person activating switch.
- Multipurpose push button.
- External dimensions 5.4" H x 4.1" W x 1.46" D.
- Three year guarantee against breakage of polycarbonate in normal use (one year on electromechanical and electronic components).

Design

- Operating modes: Key-to-Reset, Momentary or Turn-to-Rest
- Button is recessed within a durable polycarbonate housing to help prevent false activation.
- Versatile mounting plate fits North American single-gang, double-gang and four-square electrical boxes, and European electrical box.
- Easily integrates into an existing setup without the need for complex adjustments or modifications.
- Simple reset after activation.
- Indoor rated.

Construction

- Durable polycarbonate with sleek, low-profile design.

Electronics

- 1 DPDT (2 Form C) dry contact switch with NO/NC contacts, rated for 30 VAC/VDC at 5 A.
- IP camera option: up to 5 MP HD @ 30 frames per seconds, 180° field of view (diagonal), 12 VDC.

Options

- Colors available: red, green, yellow, white, blue or orange.
- Standard or custom activation labeling.
- Flush or surface mount.
- Shield, cover and/or IP camera for additional security.

PRODUCT OVERVIEW

This innovative push button features an optional camera and a unique design. The camera is designed to capture video of an individual interacting with the button, as well as their movements before and after activating the unit. The button operation modes are offered in Key-to-Reset, Momentary or Turn-to-Reset, allowing flexibility for any application. Choices include six shell colors, standard or custom wording (in any language), protective covers, and an IP camera for added identification.

HOW THEY WORK

Because of the push button's superior design combined with quality construction throughout, you can expect outstanding performance for years to come. The push button is recessed within the durable polycarbonate housing to help protect against accidental activation and provide reliable performance even in challenging environments. The rugged polycarbonate design makes it an ideal choice for indoor use. The button with the IP camera option is for daylight and low-light use and helps identify who activated the station.

STI G3 Multipurpose Push Button

Dimensions and Technical Information

G3 - -

Camera
 A - No camera
 C - With camera (includes back box)

Color
 0 - Red
 1 - Green
 2 - Yellow
 3 - White
 4 - Blue
 5 - Orange*

* STI-14010, 14020, 14210, & 14220 - Not available in orange

Cover
 0 - No Cover
 2 - Shield
 A - Shield with sound
 3 - 14010 Flush without sound**
 4 - 14020 Flush with sound**
 7 - 14210 Surface without sound
 8 - 14220 Surface with sound

Not available for **Camera option C

Button Function
 2 - Key-To-Reset
 5 - Momentary
 9 - Turn-To-Reset

Accessories
KIT-H18090 High-Security lock assembly with (2) keys
KIT-T3P Terminal Connectors (2 pack)
KIT-G3-A-EN Audio/Visual Tamper Alert - English
KIT-G3-A-ES Audio/Visual Tamper Alert - Spanish
KIT-G3-A-FR Audio/Visual Tamper Alert - French
KIT-G3-2-EN G3 GF Shield Add-On Kit - English
KIT-G3-2-ES G3 GF Shield Add-On Kit - Spanish
KIT-G3-2-FR G3 GF Shield Add-On Kit - French
KIT-G3A-BB Gray back box for G3 Series no camera, w/2 - 1/2" NPT Plug
KIT-G3C-BB Gray back box for G3 Series w/ camera, w/2 - 1/2" NPT Plug
KIT-G3-NPT-6 1/2" NPT Plug - Gray

Language
 EN - English
 ES - Spanish
 FR - French
 ZL - Custom

Text
 AB = ABORT
 EM = EMERGENCY
 EX = EMERGENCY EXIT
 PO = EMERGENCY POWER OFF
 ES = EMERGENCY STOP
 EV = EVACUATION
 XT = EXIT
 PS = FUEL PUMP SHUT-DOWN
 HV = HVAC SHUT-DOWN
 LD = LOCKDOWN
 PL = POLICE
 PX = PUSH TO EXIT
 RM = Running Man Symbol
 NT = No Text
 ZA = Custom Text

APPROVALS & WARRANTY

TESTING

- It has been tested and approved or listed by:
- UL/cUL Listed No. S7255
 - ADA Compliant
 - National Defense Authorization Act (NDAA)
 - Indoor use 14 to 120°F (-10 to 49°C)

WARRANTY

Three year guarantee against breakage of polycarbonate in normal use (one year on electromechanical and electronic components).

CUSTOMIZE YOUR TEXT - text option ZA

CUSTOM TEXT FOR TOP OF SHELL: 3 LINES, 13 CHARACTERS EACH (INCLUDES SPACES)

L1														
L2														
L3														

CUSTOM TEXT FOR BOTTOM OF SHELL: 1 LINE, 13 CHARACTERS EACH (INCLUDES SPACES)

L1														
----	--	--	--	--	--	--	--	--	--	--	--	--	--	--

CUSTOM TEXT COVER 3, 4, 7, 8: 1 LINE, 13 CHARACTERS EACH (INCLUDES SPACES)

L1														
----	--	--	--	--	--	--	--	--	--	--	--	--	--	--



Safety Technology International

2306 Airport Road info@sti-usa.com
 Waterford, MI www.sti-global.com
 48327, USA Tel:248-673-9898

Taylor House
 34 Sherwood Rd., Bromsgrove, www.sti-global.com
 Worcs., B60 3DR, England Tel: +44 (0) 1527 520 999

Unit 7A Lockheed Avenue
 Airport Business Park
 Waterford X91 HWF2 Ireland