

HD-TVI Product Sheet

2MP Economical Lineup (IR)

2MP HD-TVI IR Bullet and Dome Cameras 2.8mm fixed lens



VLB9

- IR Range: 65FT (depending on scene reflection)
- Supports up to 2MP @ 30fps
- Full HD resolution over coax
- Junction Box included



2.8-12mm motorized lens



VLD9M

- IR Range: 98FT (depending on scene reflection)
- Supports up to 2MP @ 30fps
- Full HD resolution over coax
- Junction Box included



2MP HD-TVI Turret Cameras 2.8-12mm varifocal motorized lens



VLDT3WM | VLDT3GM

- 1/2.9" 2MP Sony CMOS
- Supports multiple video signal outputs (TVI/AHD/CVI/CVBS)
- 18 built-in IR LEDs
- Junction Box included



4MP Economical Lineup (IR)

4MP HD-TVI IR Dome Camera 2.8mm fixed lens



VLT4DG

- Supports up to 4MP @ 15FPS
- Digital Wide Dynamic Range
- Junction Box included
- TAA Compliant for US Government projects



4K Economical Lineup (IR)

4K HD-TVI Cameras 2.8-12mm motorized lens



H8B8M/H8D8M/H8T8M

- IR Range: - 65FT (depending on scene reflection)
- Supports up to 8MP @ 15fps
- Digital Wide Dynamic Range
- Signal distance up to 1600 feet



Economical Recorder

HD-TVI Digital Video Recorders, 2-10TB Storage

- D4VN**
4 Channel HD-TVI Digital Video Recorder
- D8VN**
8 Channel HD-TVI Digital Video Recorder
- D16VN**
16 Channel HD-TVI Digital Video Recorder



Available in wall mount configuration

- H.264/H.265 video compression
- 4MP max recording resolution @ 10fps

- UTC function allows for zoom/focus and OSD control over coax



Low Light Solutions - Color by Day, Color in Low Light

2MP HD-TVI Intensifier® T Indoor Dome Camera 2.8-12mm auto iris varifocal lens



CVC6246T/CVC6246TW

- 3 axis lens mount
- 1/3" Sony Exmor CMOS, 2MP
- Amplify existing light with no distance limitations
- Signal distance up to 1600 ft.



2MP HD-TVI Intensifier® Bullet and Dome Camera 2.8-12mm varifocal lens/ 2.8-12mm motorized lens



HT7246T2/
HTI70TM/
HTI702TM

- Full OSD operation through on-board control and UTC (up the coax)
- Full HD resolution over coax (HD-TVI)
- True WDR operation



2MP HD-TVI Intensifier® Turret Camera 2.8-12mm motorized/3.6mm fixed lens



HTINT60TM/
HTINT601TA

- Supports up to Full HD 1080p @ 30fps
- True WDR operation
- Superior low-light performance
- Amplify existing light with no distance limitation



1000TVL Intensifier® Dome Camera 2.8-12mm varifocal lens



HTINT59K1

- 1/3" 1.3MP Sensor
- Superior low-light performance
- Built-in heater and anti-fog glass reduces condensation
- 1000 TV lines highest resolution in analog



4MP HD-TVI Flexible Intensifier® Bullet and Dome Camera 2.7-12mm motorized lens



H4FD2M/H4FB2M

- Flexible Intensifier Technology® fits any lighting application
- Supports 4MP @ 30fps (default)
- IR range: up to 98FT (depending on scene reflection)
- Motorized Lens with autofocus



Economical Recorder

Hybrid Digital Video Recorder, 2-32TB Storage

- H6HRLN**
6 Channel Hybrid Digital Video Recorder
4 Configurable Hybrid Channels (TVI or IP)
plus 2 IP Channels
- H16HRLN**
16 Channel Hybrid Digital Video Recorder
8 Configurable Hybrid Channels (TVI or IP)
plus 8 IP Channels
- H24HRLN**
24 Channel Hybrid Digital Video Recorder
8 Configurable Hybrid Channels (TVI or IP)
plus 8 IP Channels plus 8 TVI Channels



Available in wall mount configuration

- Supports up to 5MP (HD-TVI + IP) on all channels and 4K (IP) on 8 channels

- H.265 compression - Store up to 2x more than H.264

- 4K HDMI out and VGA monitor output

NDA A Compliant Products are in compliance with NDA A Section 889 Part B Guidelines

Get complete specifications and see the entire line of products at:
www.specotech.com

Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation.
REV. 4/1/2024

speco
technologies