

Product data sheet

Specifications



APC Smart-UPS X, Line Interactive, 1000VA, Rack/tower convertible 2U, 120V, 8x 5-15R NEMA, SmartConnect port, Extended runtime

SMX1000C

Overview

Lead time	Usually Ships within 2 Weeks
-----------	------------------------------

Main

Product or Component Type	Uninterruptible power supply (UPS)
---------------------------	------------------------------------

Complementary

Communication port type	SmartConnect Ethernet port SmartSlot
-------------------------	---

Software package	SmartConnect software for remote power monitoring feature availability varies by terms of use
------------------	---

Batteries & Runtime

Run Time	View Runtime Graph
----------	------------------------------------

Efficiency	View Efficiency Graph
------------	---------------------------------------

Battery Type	Lead-Acid battery
--------------	-------------------

Extendable Run Time	1
---------------------	---

Included Battery Modules	0
--------------------------	---

Battery Slots Empty	0
---------------------	---

Typical recharge time	3 h
-----------------------	-----

RBC Quantity	1
--------------	---

Overcurrent protection	60 A
------------------------	------

Battery life	3...5 ms
--------------	----------

Replacement battery	APCRBC116
---------------------	---------------------------

Battery Charge Power (Watts)	99 W rated
------------------------------	------------

General

Provided equipment	Installation guide Rack Mounting brackets Removable support feet Smart UPS signalling RS-232 cable USB cable Cat 5 ethernet cable
--------------------	--

Number of power module	0
------------------------	---

Number of power module filled slots	0
-------------------------------------	---

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Number of power module free slots	0
product web sub-family	Extended run
Redundant	No

Physical

Number of rack unit	2U
Cable length	8 ft (2.4 m)
Number of cables	1
color	Black
Height	17.01 in (43.2 cm)
Width	3.50 in (8.9 cm)
Depth	19.29 in (49 cm)
Product Weight	50.40 lb(US) (22.86 kg)
Mounting preference	Lower
Mounting Mode	Rack-mounted with kit
Two post mountable	1
USB compatible	Yes

Input

Main Input Voltage	120 V
Input Connection Type	NEMA 5-15P
Maximum Input Current per Phase	12 A
Switching current capacity	15 A
Efficiency at full load	82...143 V
Input Frequency	50/60 Hz +/- 3 Hz auto-sensing

Output

Main Output Voltage	120 V
Kw Rating	900 W
Rated power in VA	1000 VA
output connection type	8 NEMA 5-15R
Harmonic distortion	Less than 5%
Maximum configurable power in VA	1000 VA
Max Configurable Power (Watts)	900 W
Topology	Line Interactive
Waveform Type	Sine wave
Full load runtime	00:07:15 900 W
Half load runtime	00:19:48 450 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains

Conformance

Product Certifications	cUL Listed ENERGY STAR V2.0 (USA)
Equipment protection policy	Lifetime : \$150000

Environmental

Acoustic level	40 dBA
Online Thermal Dissipation	82 Btu/h
Operating altitude	0...10000 ft
Ambient air temperature for operation	32...104 °F (0...40 °C)
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)
Relative Humidity	0...95 %
Storage Relative Humidity	0...95 %

Communications & Management

control panel	Multi-function LCD status and control console
Emergency Power Off (EPO)	Yes
Free slots	1
Communication port support	SmartConnect Ethernet port: for cloud monitoring feature availability varies by terms of use
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rating	600 J
Filtering	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : mee

Ordering and shipping details

GTIN	731304401124
Country of origin	PH

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	23.19 in (58.9 cm)
Package 1 Width	24.41 in (62 cm)
Package 1 Length	9.69 in (24.6 cm)
Package 1 Weight	60.23 lb(US) (27.32 kg)

Contractual warranty

Warranty	3 years repair or replace for hardware. 2 years for battery, plus 1 additional year if customers registers device to SmartConnect
----------	---

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	1206
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
REACH Regulation	REACH Declaration

Energy efficiency	
 ENERGY STAR®	ENERGY STAR UPS V2.0 (USA)

Use Again

Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	No
WEEE	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Image of product / Alternate images

Alternative



