



3188SB

VANDALCOM ELECTRONIC KEY



Made using double 2.5 mm 316 stainless steel plate. Complete with backlit keypad. Features 300 different 8-digit codes that can be programmed from the keypad to control two relays (10A), as well as a confirm request buzzer and relay activation LED. Relay closure time can be set from the keypad. Dimensions: 106x106x56 mm.



3188SB

VANDALCOM ELECTRONIC KEY

MAIN FEATURES

Supply voltage	12VAC/22VDC
Vandal Resistant rating (IK code)	IK10
Operating humidity (RH max) (%)	25 ÷ 95
Backlight color	White

GENERAL DATA

Height (inch) (in)	4.17
Width (inch) (in)	4.17
Depth (inch) (in)	2.2
Type of finishing materials	Steel
Product color	Steel
Operating temperature (°F)	-13 ÷ 131

COMPATIBILITY

Simplebus 2 audio/video system	Yes
Simplebus 2 audio system	Yes
Building Kit audio/video system	Yes
Vip system	Yes
Simplebus 1 audio system	Yes
Access Control system	Yes

ELECTRICAL SPECIFICATIONS

Absorption in stand-by (mA)	20
Absorption with 1 bistable relay activated (mA)	45
Absorption with 2 bistable relays activated (mA)	65

SOFTWARE/FIRMWARE SPECIFICATIONS

Number of user codes (n°)	300
---------------------------	-----



3188SB

VANDALCOM ELECTRONIC KEY

HARDWARE SPECIFICATIONS

Visual signalling	Yes
Acoustic signalling	Yes

MOUNTING/INSTALLATION

Flush-mounted	Yes
---------------	-----