

# Product data sheet

Specifications



## APC Back-UPS, 1050VA/600W, Floor/Wall Mount, 120V, 8x NEMA 5-15R outlets, USB Type A + C Ports

BE1050G3

### Overview

Lead time Usually in Stock

### Main

Main Input Voltage	120 V
Main Output Voltage	120 V
Kw Rating	600 W
Rated power in VA	1050 VA
Product or Component Type	Uninterruptible power supply (UPS)
Input Connection Type	NEMA 5-15P
output connection type	6 NEMA 5-15R 2 NEMA 5-15R surge
Cable length	5 ft (1.5 m)
Number of cables	1
Battery Type	Lead-Acid battery
Provided equipment	User Manual USB cable
Range of Product	Back-UPS

### Batteries & Runtime

Run Time	<a href="#">View Runtime Graph</a>
Efficiency	<a href="#">View Efficiency Graph</a>
Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	8 h
Battery Charge Power (Watts)	13 W rated
Battery power in VAh	108 VAh runtime
Battery life	2...5 year(s)
Replacement battery	<a href="#">APCRBC164</a>
Battery graph comments	This graph is based on actual measured runtime data. All measurements were taken with new, fully charged batteries and a balanced resistive load (PF = 1.0). Actual runtimes may vary from the values of this graph. Actual runtimes are dependent on several variables including battery age, battery charge level, environmental conditions and characteristics of the connected load.
Extendable Run Time	0

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

## General

Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

## Physical

color	Black and white
Height	3.54 in (9 cm)
Width	6.57 in (16.7 cm)
Depth	12.52 in (31.8 cm)
Product Weight	9.5 lb(US) (4.3 kg)
Mounting preference	No preference
Mounting Mode	Not rack-mountable
Two post mountable	0
USB compatible	No

## Input

Input Frequency	50/60 Hz +/- 3 Hz auto-sensing
Efficiency at full load	92...139 V

## Output

Max Configurable Power (Watts)	600 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Topology	Standby
Waveform Type	Stepped approximation to a sinewave
Maximum configurable power in VA	1050 VA
Transfer Time	6ms typical : 10ms maximum

## Conformance

Product Certifications	cTUVus ENERGY STAR V2.0 (USA)
------------------------	----------------------------------

## Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	10...90 %
Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)
Acoustic level	45 dBA
Online Thermal Dissipation	19.249 Btu/h

## Communications & Management

---

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
control panel	LED Status display with On Line : On Battery

---

## Surge Protection and Filtering

---

Surge energy rating	490 J
---------------------	-------

---

## Ordering and shipping details

---

GTIN	731304625384
------	--------------

---

## Packing Units

---

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.86 in (22.5 cm)
Package 1 Width	6.06 in (15.4 cm)
Package 1 Length	15.04 in (38.2 cm)
Package 1 Weight	10.6 lb(US) (4.8 kg)
SCC14	10731304625381

---

## Contractual warranty

---

Warranty	3 years repair or replace
----------	---------------------------

---

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard

No

Packaging without single use plastic

No

[EU RoHS Directive](#)

Compliant with Exemptions

REACH Regulation

[REACH Declaration](#)

### Energy efficiency

 [ENERGY STAR®](#)

ENERGY STAR UPS V2.0 (USA)

## Use Again

### Repack and remanufacture

[Circularity Profile](#)

[End of Life Information](#)

Removable battery

User replaceable

Take-back

No

Offer Marketing Illustration

Product benefits / Features

---



Image of product / Alternate images

Alternative

---

