



CM491-series & CM492-series Vandal Resistant Apartment Entry Panels

IL500 Specification Sheet

Tek-ENTRY® Apartment Entry Systems • Rev. 10 - 12/2013

Features

- Vandal resistant panel and push button actuators
- Weather resistant Mylar speaker
- Fully enclosed back box with knockouts
- Hands-free loudspeaker (or optional handset)
- Engraveable solid aluminum push button actuators
- Vandal resistant Lexan directories
- Slim-line surface mount frame option
- Tamper resistant mounting screws

Description

The CM491-series vandal resistant apartment entry panel is available with 4, 8, 12, 16 or 20 buttons and includes an integral directory.

The CM492-series vandal resistant apartment entry panels are modular so that adding additional button panels (if required), directory panels, frame and housing will comprise a complete entrance panel.

Panels are equipped with a Mylar voice-frequency response speaker protected by a louvered grill and perforated aluminum material. The aluminum push button actuators may be engraved with up to four letter/digit combinations.

Specifications

Dimensions:	Height: 16.5" (418 mm)
	Width: 4" (100 mm)
Speaker:	2.5" (63.5 mm) Mylar
Construction:	Modular extruded anodized aluminum
Flush Mount:	CM491: OF291 frame, OH191 housing
	CM492: OF190-series frame, OH190-series housing
Surface Mount:	CM491: OF291S frame
	CM492: OF190S-series frame
Plungers:	Engraved extruded aluminum
Push Button:	Individually replaceable with self-wiping contacts



CM491/016
OF291 Frame



CM492/024
OF192 Frame and
AM190D Directory

CM491-series & CM492-series Vandal Resistant Apartment Entry Panels

Required Components

IR-series Speaker-type Remote Stations
PK543A Apartment Intercom Amplifier
RP055EN Apartment Number Button Engraving
SS102A or SS106 Transformer

For CM491-series, add:
OF291 Frame and OH191 Housing, or OF291S Frame

For CM492-series, add:
AM190D Directory Panel
OF190-series Frame and OH190-series Housing, or
OF190S-series Frame

www.tektone.com

277 Industrial Park Road • Franklin, NC 28734 • tektone@tektone.net

Phone: (828) 524-9967 • Fax: (828) 524-9968 • Sales: Choose option 2 • Tech Support: Choose option 3

TekTone®'s quality system is registered by UL® to the ISO 9001 standard. (Reference #10001510.)