Specifications





Eaton EMA107-10

Eaton Managed PDU, 1PH, 0U, NEMA L6-30P input, 10 ft cord, 5.76kW, 24A, 200-240V, 24 Outlets (20) C13 (4) C19, TAA

General specifications	
PRODUCT NAME	Eaton managed PDU
CATALOG NUMBER	EMA107-10
UPC	743172069184
PRODUCT LENGTH/DEPTH	2 in
PRODUCT HEIGHT	66.5 in
PRODUCT WIDTH	2.1 in
PRODUCT WEIGHT	17.3 lb
WARRANTY	3 year
COMPLIANCES	TAA Compliant
CERTIFICATIONS	UL Listed

Powering Business Worldwide

Product specifications

FORM FACTOR	0U (Vertical)
OUTLET CONTROL	Yes
PHASE	Single-phase
WATTAGE	5.76 kW max
AMPERAGE RATING	24A
INPUT VOLTAGE	200-240V
INPUT CONNECTION	L6-30P
OUTLETS	(20) C13 Outlet grip, (4) C19 Outlet grip
CORD LENGTH	10 ft
FREQUENCY RATING	50-60 Hz
SERIAL INTERFACE	RS-232
OPERATING TEMPERATURE	0° to 60°C (32° to 140°F)

Resources

CERTIFICATION REPORTS	Eaton ePDU certificate of volatility Eaton RoHS Declaration of Conformity: ePDU G3
DRAWINGS	Eaton Advanced Monitored and Managed ePDU visio stencil Eaton ePDU Managed EMA107-10 technical drawing
MANUALS AND USER GUIDES	Eaton ePDU G3 operations manual Eaton ePDU G3 replace and configure eNMC module Eaton ePDU G3 1U and 2U installation addendum Eaton ePDU G3 instruction set - system objects Eaton Double-wide G3 ePDU installation and connectivity quick start guide
SERVICE AND TROUBLESHOOTING	EMA107-10 eNMC replacement configuration file

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.