

Product data sheet

Specifications



Device monitoring and management, Network Management Cards, NMC3 with Environmental Monitoring and Modbus, secure remote UPS monitoring and management

AP9643

Overview

Lead time Usually in Stock

Main

Range of Product Network Management Cards

Range Compatibility Galaxy VM
Galaxy VX
Symmetra PX
Smart-UPS
Smart-UPS Ultra
Smart-UPS On-Line
Smart-UPS Modular Ultra
Smart-UPS Battery Systems
Back-UPS SX3
Refurbished Smart-UPS

Product or Component Type Device monitoring and management

Provided Equipment Temperature Sensor
Micro-USB cable
Installation manual

Number of input phases 1
3

Standards EN 61000-4-2
BS EN 61000-4-2
EN 61000-4-3
BS EN 61000-4-3
EN 61000-4-4
BS EN 61000-4-4
EN 61000-4-5
BS EN 61000-4-5
EN 61000-4-6
BS EN 61000-4-6
EN 61000-4-8
BS EN 61000-4-8
EN 61000-4-11
BS EN 61000-4-11
BS EN 55024
EN 55035
BS EN 55035
EN 62040-2
BS EN 62040-2
EN 55011:A1
EN 55024:A1
EN 55032:class A
VCCI class A
ICES-003:issue 6
BS EN 55032:class A
BS EN 55011:A1

General

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Variant option	Environmental monitoring with Modbus
----------------	--------------------------------------

Physical

Product Weight	0.31 lb(US) (0.14 kg)
Width	4.76 in (12.1 cm)
Height	1.50 in (3.8 cm)
Depth	4.25 in (10.8 cm)

Conformance

Product Certifications	FCC Class A AS/NZS
------------------------	-----------------------

Environmental

Storage Relative Humidity	0...95 %
Relative Humidity	0...95 %
Ambient Air Temperature for Storage	5...149 °F (-15...65 °C)
Ambient air temperature for operation	23...113 °F (-5...45 °C)
Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)
Operating altitude	0...10000 ft

Communications & Management

Communication Network Type	10/100/1000BASE-T
Authentication	Radius Lightweight Directory Access Protocol (LDAP)
Communication Port Protocol	HTTP over secure sockets Layer (HTTPS) SSH FTP HTTP SNMP DHCP BOOTP (Bootstrap Protocol) TCP/IP

Ordering and shipping details

GTIN	731304403319
------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.01 in (5.1 cm)
Package 1 Width	6.26 in (15.9 cm)
Package 1 Length	9.25 in (23.5 cm)
Package 1 Weight	2.006 lb(US) (0.91 kg)



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) **195**

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard **No**

Packaging without single use plastic **No**

[EU RoHS Directive](#) **Compliant**

SCIP Number **F4c2965e-f80d-4830-8cd4-be926afb0f45**

Use Again

Repack and remanufacture

Circularity Profile [End of Life Information](#)

Removable battery **Yes**

Take-back **No**

WEEE  **The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**