



RapidRun® is designed to be the standard for in-wall audio/video installations. Using pre-terminated Break-away flying leads and wall plates with an in-wall runner ensures flexible, efficient, high quality connections for all types of equipment, with no field terminations.

Use this CMG-rated Multi-Format Runner for in-wall installations that support high density, multi-format applications. Whether hanging a projector in a modern 21st century classroom or installing a commercial digital signage system, a clean, crisp signal will be delivered every time.

Please note: This product is designed to extend an existing RapidRun Multi-Format Runner cable. While this product can provide a solution for longer length installations, common signal limitations should be observed.

<

## Features & Benefits

Designed for use with RapidRun Multi-Format runner cables

Compatible with RapidRun Multi-Format VGA wall plates and flying leads

28 AWG and 24AWG conductor construction

## Specifications

### General Info

Product Line	C2G	Color	Black
UPC Number	757120600817	Country Of Origin	China
Application Sector	Commercial, Residential	Warranty Type	Lifetime
Type	Adapter, Cable		

### Dimensions

Product Length US	1.5 FT	Cable Length	1.5 ft
-------------------	--------	--------------	--------

### Technical Information

Wire Gauge	24 AWG	Video Resolution	UXGA (1600x1200)
Storage Humidity	20-80% RH (Non-Condensing)	Shielded/Unshielded	Shielded

---

Jacket Rating	Standard / Non-Rated	Data Transfer Rate	18 Gbps
Connector 2	RapidRun 15-pin Male	Connector 1	VGA Male
Video Output Support	VGA	Operating Temperature	-20°-80°C
Video Input Support	VGA	Storage Temperature	-20° - 80° C

---