

VerifEye™ Communication Products Power Supply



DESCRIPTION

The VerifEye™ Communication Products Power Supply (YBM07) is used to power VerifEye communication products and replaces the YBM05. The YBM07 utilizes flying leads versus a Phoenix Connector as previously used by Leviton.

The YBM07 is not included with VerifEye communication products and **must** be ordered separately.

APPLICATIONS

- For use with:
 - (A8810) EMB Hub
 - (A7810) EMB Hub Lite
 - (A8332) Flex I/O Module
 - (A8911) HD Pulse Module

SPECIFICATIONS	
Input	100-240V, 600mA max, 50-60 Hz
Output	+24VDC, 1A max, regulated
Output Power Max	24W
Output connection	UL1015, 18AWG, stripped and tinned 10mm, red positive (+) and black negative (-) flying leads
Operating Temperature Range	32-104°F (0-40° C)
Listings	UL Listed 17DU E248122, ITE power supply, RoHS compliant, Class II

ORDERING INFORMATION

CAT. NO.	DESCRIPTION
YBM07-001	VerifEye Comm Bundles Power Supply, 24VDC 1A, flying leads

Leviton Mfg. Co., Inc. Lighting & Energy Solutions

20497 SW Teton Avenue, Tualatin, OR 97062 1-800-736-6682 Tech Line: 1-800-959-6004 Fax: 503-404-5594 www.leviton.com/les
 © 2015 Leviton Manufacturing Co., Inc. All rights reserved. Subject to change without notice.*

G-9466/D15-aa