



Tek-ENTRY® Modular Series Telephone Entry Systems Specification Sheet

IL580
Section A
Rev. 8 - 08/2010



FEATURES

TekTone®'s Tek-ENTRY® Modular Series Telephone Entry Systems are designed for easy operation. All models have a capacity of 1-750 suites, and may be configured for 7-, 10- or 11- digit telephone numbers

By entering a simple 4-digit code, the system calls the correct phone number to allow access. The called party's phone number remains secret. Programming and re-programming are push-button simple.

- 3-year warranty (control unit only)
- Use with rotary or touchtone service
- Memory retention during power failure (EEPROM)
- 26-bit Wiegand output to connect to card reader systems
- Toll restrictor
- Front-panel programming
- Tamper-proof programming security
- Aluminum construction resists vandalism
- Unbreakable Lexan® Directory Window*
- Selectable 1-9 minute talk time limit

SPECIFICATIONS

Dimensions: Height: 19" (483 mm)
Width: refer to IL312 housing chart
Depth: .875" (22 mm) flush-mounted
Construction: Anodized extruded aluminum
Power Required: 110 VAC with SS106 Transformers

REQUIRED COMPONENTS

AM190D	Directory Panel (60 names each max)
OF190 Series	Frame
OH190 Series	Housing
SS106	Transformer (2 required)
TE905A	Modular Telephone Entry Panel
-or-	
TE905ANP	No Phone Line version Telephone Entry Panel
TA905	Optional Handset Panel
Suffix "P"	Postal Release Option, installed

* Note: Lexan® is a Registered Trademark of the General Electric Corporation.

ARCHITECTS' AND ENGINEERS' SPECIFICATION

TekTone®'s Tek-ENTRY® Modular Series Telephone Entry System is a complete automatic call and entry control system. The system operates on a standard dedicated telephone line and 110 VAC with 16 VAC transformer.

All units shall include integral power supply, panel-mounted PC board, metal telephone key pad, busy and door-open indication, postal release option and speaker/microphone panel, or optional armored handset. The Tek-ENTRY® Modular Series allows for a capacity of 1-750 suites, and may be configured for 7-, 10- or 11-digit telephone numbers.

The Tek-ENTRY® Modular Series System shall provide a relay output for controlling doors, gates, elevators, etc., and shall be able to dial either rotary or touchtone. It shall also provide built-in capability for multiple entrances. Construction shall be of extruded anodized aluminum modular panels.

www.tektone.com

277 Industrial Park Road • Franklin, NC 28734 • tektone@tektone.net
Phone: (828) 524-9967 • Fax: (828) 524-9968 • Tech Support: Choose option 2 • Sales: Choose option 3
TekTone®'s quality system is registered by UL® to the ISO 9001 standard. (Reference #10001510.)