



EK117 / EK117B Emergency-Call (Call for Assistance) Kit(s)



NOTE: Image shown is with Pull Cord Station Activated

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The Emergency (Call for Assistance) kit(s) shall be Alpha Communications® **EK117** (without buzzer) or **EK117B** (with buzzer/horn) or approved equal. Dome lights shall include a translucent plastic cover mounted on a flame retardant ABS plastic panel, and shall mount over a conventional 1 or 2-gang electrical back box. Dome lights shall feature Hi-Brightness LEDs to eliminate costly bulb replacement, and minimize downtime.

The Emergency Call switch shall be mounted on a durable ABS plastic faceplate marked "EMERGENCY". Signaling for assistance shall only require a short pull in any direction on the 6' nylon cord. Canceling the call shall be possible only at the point of origin. Unit shall mount on single-gang electric "gem" box or plaster ring, and shall feature a RED 'call placed' Indicator when activated.

The built-in buzzer/horn (in the **EK117B** kits) shall sound as long as the dome light is lighted (activated).

Contractor shall observe all local and national electrical and building codes.

EK117 / EK117B EMERGENCY-CALL KITS

The Alpha Communications® **EK117** and **EK117B** Emergency-Call Kits are the ideal solution for a stand-alone 'Call for Assistance' applications where an emergency switch is required. Typically these kits are ideal for use in health care facilities, public rest-rooms (toilets) and handicapped areas. These new and improved kits now feature Dome Lights with Hi-Brightness White LEDs so there is no need for costly bulb replacements!

The model **EK117** consists of:

- 1- **SF117/2A** Emergency Pull Cord station (RED Indicator style)
- 1- **SS106** 24VAC (U.L Listed) pigtail Transformer
- 1 - **CDL101LED** Corridor Dome Light (LED type - without a buzzer).

The model **EK117B** consists of

- 1- **SF117/2A** Emergency Pull Cord station (RED Indicator style)
- 1- **SS106** 24VAC (U.L Listed) pigtail Transformer
- 1 - **CDL123B** Corridor Dome Light (LED type - with a built-in buzzer/horn).

FEATURES

- Ideal for 'Toilet Alarm' or other Stand-Alone application
- Hi-Brightness White LEDs - No Bulb Replacement!!
- Safe - Low Voltage Wiring

DOME LIGHT SPECIFICATIONS

Dimensions:	Height: 5.20" (133mm) Width: 4.55" (116mm) Projects: 3.50" (89mm) from mounting surface
AC Current:	EK117: 24VAC, 10mA EK117B: 24VAC, 170mA
Mounting:	Fits standard 1 or 2-gang box. Minimum depth of box to be no less than 1.75".
Finish:	Translucent white plastic cover mounted on a flame retardant, fog white ABS plastic panel.

PULL CORD SPECIFICATIONS

Dimensions:	Height: 4.50" (114mm) (less cord) Width: 2.75" (70mm) Depth: 1.50" (38mm) (into wall)
Faceplate:	White ABS (flame retardant) plastic.
Connection:	Pigtail wire leads
Mounting:	Standard single-gang electrical box
Marking:	"EMERGENCY" in Black Letters

Call Placed Notification:	Sliding Red Window Type
----------------------------------	-------------------------

Alpha Communications

42 Central Drive • Farmingdale • NY • 11735-1202 • Phone: (631) 777-5500 • Fax: (631) 777-5599
TOLL-FREE: (800) 666-4800 • Web: www.alphacommunications.com • Email: info@alphacommunications.com

Copyright© 1998-2023 Alpha Communications® - All Rights Reserved.

Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.