

Product data sheet

Specifications



APC Smart-UPS RT 192V RM Battery Pack



SURT192RMXLBP3U

Overview

Lead time Usually in Stock

Main

Main Input Voltage 208 V

Product or Component Type Battery

Main Output Voltage 208 V

Number of rack unit 3U

Number of cables 1.0

Battery Type Lead-Acid battery

Provided Equipment Installation guide
Rack Mounting brackets
User Manual

Range of Product Smart-UPS Battery Systems

Batteries & Runtime

Battery blocks per string 16

Battery Slots Empty 0

Included Battery Modules 4

Device mounting Stand alone battery stack

Battery Voltage 192V

Additional information Replace all batteries in operation together (UPS internal and external batteries) all-at-once

RBC Quantity 2

Replacement battery [APCRBC140](#)

Physical

Color Black

Height 5.12 in (13 cm)

Width 17.01 in (43.2 cm)

Depth 25.98 in (66 cm)

Product Weight 200.42 lb(US) (90.91 kg)

Mounting Mode Rack-mounted

USB compatible No

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Conformance

Standards	OSHDP
-----------	-------

Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
---------------------------------------	-------------------------

Operating altitude	0...10000 ft
--------------------	--------------

Relative Humidity	0...95 % non-condensing
-------------------	-------------------------

Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
-------------------------------------	--------------------------

Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)
------------------	--

Storage Relative Humidity	0...95 % non-condensing
---------------------------	-------------------------

Ordering and shipping details

GTIN	731304259336
------	--------------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	16.26 in (41.3 cm)
------------------	--------------------

Package 1 Width	39.37 in (100 cm)
-----------------	-------------------

Package 1 Length	23.62 in (60 cm)
------------------	------------------

Package 1 Weight	223.46 lb(US) (101.36 kg)
------------------	---------------------------

Contractual warranty

Warranty	2 years repair or replace, optional on-site warranties available, optional extended warranties available
----------	--

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) 464

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Pro-active compliance (Product out of EU RoHS legal scope)

SCIP Number A64c500c-f72a-458b-8faa-8175a94429fe

REACH Regulation [REACH Declaration](#)

California proposition 65 **WARNING:** This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Again

Repack and remanufacture

Circularity Profile [End of Life Information](#)

Removable battery User replaceable

Take-back Yes