Specifications

Eaton EMA113-10



Catalog Number: EMA113-10

Eaton Managed rack PDU, 0U, 5-20P, L5-20P input, 1.92 kW max, 120V, 16A, 10 ft cord, Single-phase, Outlets: (8) 5-20R - TAA compliant

General specifications

Product Name	**Catalog Number**
Eaton managed PDU	EMA113-10
UPC	**Product Length/Depth**
743172079176	35.5 in
Product Height	**Product Width**
2.05 in	2.56 in
Product Weight	**Warranty**
6.5 lb	3 year
Compliances	**Certifications**
TAA Compliant	UL Listed

Powering Business Worldwide

Product specifications

Form factor
0U (Vertical)

Outlet control
Yes

Phase
Single-phase

Wattage
1.92 kW max

Amperage Rating
16A

Input voltage
120V

Input connection
5-20P, L5-20P

Outlets
(8) 5-20R

Cord length
10 ft

Frequency rating
50-60 Hz

Serial interface
RS-232

Operating Temperature
0° to 60°C (32° to 140°F)

Resources

Certification reports
Eaton ePDU certificate of volatility

Eaton RoHS Declaration of Conformity: ePDU G3

Drawings
Eaton Advanced Monitored and Managed ePDU visio stencil

Eaton ePDU Managed EMA113-10 technical drawing

Manuals and user guides
Eaton ePDU G3 replace and configure eNMC module

Eaton ePDU G3 instruction set - system objects

Eaton ePDU G3 operations manual

Eaton ePDU G3 1U and 2U installation addendum

Eaton Double-wide G3 ePDU installation and connectivity quick start guide

Service and troubleshooting
EMA113-10 eNMC replacement configuration file

Specifications and datasheets
Eaton Specification Sheet - EMA113-10

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia