

netSELECT
Jacks
Category 6A Jack

HUBBELL

Features

- Cost effective solution supporting IEEE 802.3 10Gbe applications
- Fast, Reliable Cobra-Lock termination with no punchdowns or special tools
- Supports POE, tested above the IEEE 802.3bt 4PPoE Standard
- UL 2043 Listed for use in plenum (air handling) spaces
- Universal wiring label - one jack for T568A or T568B wiring

Ordering Information

| Description | Color | Catalog Number | UPC |
|--|-------|----------------|--------------|
| netSELECT Category 6A Jack, Universal TIA568A/B Wired, Red | Red | NSJU6AR | 883778507373 |



Listings

ANSI/TIA-568.2-D Category 6A channel requirements
cULus Listed 1863
UL 2043
RoHS Compliant

Specifications

| | |
|--------------------------------|--------------------------------------|
| Housing Material | High-impact thermoplastic (UL 94V-0) |
| Nose Contacts | Copper Alloy with Gold Over Plating |
| Dimensions In (mm) (H x W x D) | 0.87 (22) x 0.67 (17) x 1.39 (35) |
| Conductor Compatibility | 24-22 AWG Solid |
| IDC Re-Termination Cycles | 25 |

Performance

Application

10BASE-T through 10GBASE-T Ethernet

Electrical Performance

TIA 568 CAT6A Channel Compliant

Plug Mating Cycles

750 Minimum

PoE Support

IEEE 802.3af, 802.3at,
802.3bt Type 3 and Type 4

Accessories

| | |
|---|----------|
| netSELECT 24 Port Unloaded Panel | NSPJ24 |
| netSELECT 48 Port Panel, Unloaded | NSPJ48 |
| CAT6A Reduced Diameter Plenum Cable, Blue | C6ASPDSB |
| CAT6A Field Termination Plug | SP6A |
| CAT6A MPTL Assembly w/ 18" Lead | SCP6A |

Online Resources

Customer Sales Drawings
eCatalog
Installation Instructions