# Power Extension Cord, NEMA L5-30P to NEMA L5-30R- Heavy-Duty, 30A, 125V, 10 AWG, 6 ft. (1.83 m), Black, Locking Connectors

MODEL NUMBER: **P046-006-LL-30A**











Extends the length of your existing power cord with NEMA L5-30P plug by 6 ft.

### Highlights

- Locking connectors prevent accidental disconnection
- Durable PVC jacket
- 6-ft. (1.83 m) long
- 125V/30A rating

### Package Includes

- P046-006-LL-30A Heavy-Duty Power Extension Cord, 6-ft. (1.83 m)

## Description

The P046-006-LL-30A Heavy-Duty Power Extension Cord features a NEMA L5-30P plug on one end and a NEMA L5-30R receptacle on the other, allowing you to extend the length of your existing power cord. Both molded connectors twist and lock into place, which prevents disconnection via jostling or other accidental impact. The 6-ft. (1.83 m) 10 AWG cord is rated for 125V and 30A. Its durable PVC jacket is designed to last a long time.

## Features

**Extends Existing Power Cord with NEMA L5-30P Plug**

- NEMA L5-30R receptacle at opposite end
- Molded locking connectors prevent accidental disconnection
- Integral strain relief
- 125V/30A rating
- Durable PVC jacket
- 6-ft. (1.83 m) long

# Specifications

| | |
|---|---|
| **OVERVIEW** | |
| UPC Code | 037332200938 |
| Device Compatibility | UPS; PDU |
| Country/Region | North America |
| **INPUT** | |
| Maximum Input Amps | 30 |

| | |
|---|---|
| Voltage Compatibility (VAC) | 125 |
| **CONNECTIONS** | |
| Side A - Connector 1 | NEMA L5-30P |
| Side B - Connector 1 | NEMA L5-30R |
| **PHYSICAL** | |
| Plug Color | Black |
| Cable Jacket Color | Black |
| Cable Jacket Material | PVC |
| Cable Jacket Rating | VW-1 |
| Power Cord Jacket Type | SJT |
| Cable Outer Diameter (OD) | 14.6mm |
| Number of Conductors | 3 |
| Wire Gauge (AWG) | 10 |
| Wire Gauge (OD - $mm^2$) | 5.26 |
| Cable Length (ft.) | 6 |
| Cable Length (m) | 1.83 |
| Cable Length (cm) | 182.88 |
| Shipping Dimensions (hwd / in.) | 11.50 x 9.00 x 0.50 |
| Shipping Dimensions (hwd / cm) | 29.21 x 22.86 x 1.27 |
| Shipping Weight (lbs.) | 1.90 |
| Shipping Weight (kg) | 0.86 |
| **ENVIRONMENTAL** | |
| Operating Temperature Range | 14° to 140°F (-10° to 60°C) |
| Storage Temperature Range | 14° to 140°F (-10° to 60°C) |
| Operating Humidity Range | 35% to 85% RH, Non-Condensing |
| Storage Humidity Range | 35% to 85% RH, Non-Condensing |
| **FEATURES & SPECIFICATIONS** | |
| Antibacterial | No |
| Angled Plug | No |
| High Voltage | No |
| Locking Plug | Yes |
| Coiled Power Cord | No |
| **STANDARDS & COMPLIANCE** | |

| | |
|---|---|
| Product Certifications | cUL Listed; UL Listed |
| Product Compliance | RoHS |
| **WARRANTY & SUPPORT** | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |

1000 Eaton Boulevard
Cleveland, OH 44122
United States
https://tripplite.eaton.com

© 2025 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.