

Product data sheet

Specifications



RACK PDU, SWITCHED, ZEROU, 12.5KW, 208V, (21)C13&(3)C19; 10 CORD

AP7998B

Overview

Lead time Usually in Stock

Main

| | |
|---------------------------|--|
| Color | Black |
| Product or Component Type | PDU |
| PDU Type | Switched |
| Cord length | 10 ft (3.05 m) |
| Number of cables | 1 |
| Provided Equipment | Cord retention bracket(s) Documentation CD Installation guide Rack Mounting brackets RS-232 configuration cable Toolless Mounting Kit |

Complementary

| | |
|----------------------------|-------------------------------------|
| Input Voltage | 208 V 3 phase |
| Height | 70.00 in (177.8 cm) |
| Width | 2.20 in (5.6 cm) |
| Output Voltage | 208 V |
| Depth | 3.50 in (8.9 cm) |
| Product Weight | 21.32 lb(US) (9.67 kg) |
| Mounting Location | Side |
| Mounting preference | No preference |
| Mounting Mode | Rack-mounted |
| Rack units | 0U |
| Mounting position | Vertical |
| Max line current | 35 A |
| Input current limits | 35 A |
| Load Capacity | 12500 VA |
| Input Frequency | 50/60 Hz |
| Number of input connectors | 1 CS8365 |
| Outlet type and quantity | 21 IEC 60320 C13 3 IEC 60320 C19 |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Environment

| | |
|--|---|
| Product Certifications | cUL Listed CSA Industry Canada UL Listed |
| Standards | FCC Part 15 class A ICES-003 UL 60950 |
| Ambient air temperature for operation | 23...113 °F (-5...45 °C) |
| Relative Humidity | 5...95 % |
| Operating altitude | 0...10000 ft |
| Ambient Air Temperature for Storage | -13...149 °F (-25...65 °C) |
| Storage Relative Humidity | 5...95 % |
| Storage altitude | 0...50000 ft (0.0000000000...15240.0000000000 m) |

Ordering and shipping details

| | |
|--------------------------|--------------|
| GTIN | 731304331667 |
| Country of origin | IN |

Packing Units

| | |
|-------------------------------------|-----------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 82.99 in (210.8 cm) |
| Package 1 Width | 5.00 in (12.7 cm) |
| Package 1 Length | 5.98 in (15.2 cm) |
| Package 1 Weight | 28.4 lb(US) (12.9 kg) |

Contractual warranty

| | |
|-----------------|---------------------------|
| Warranty | 2 years repair or replace |
|-----------------|---------------------------|



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

No

[EU RoHS Directive](#)

Compliant with Exemptions

SCIP Number

1cdb2fed-a06f-4574-913d-8df8e70936b2

REACH Regulation

[REACH Declaration](#)

Halogen content performance

Product contains halogen above thresholds

Energy efficiency

Optimized Energy Efficiency

Energy efficient product

Use Again

Repack and remanufacture

Circularity Profile

[End of Life Information](#)

Removable battery

Yes

Take-back

Yes

Image of product / Alternate images

Alternative



