

# Product data sheet

Specifications



## APC Rack PDU 9000 Switched, ZeroU, 30A, 120/208V, (16) 5-20R (7) C13/C15 (1) C19/C21

APDU9970

### Overview

Lead time Usually in Stock

### Main

Color	Black
Product or Component Type	PDU
PDU Type	Switched
Cord length	10 ft (3.05 m)
Number of cables	1
Provided Equipment	Installation guide Rack Mounting brackets Safety guide

### Complementary

Input Voltage	120 V 208 V
Height	72.01 in (182.9 cm)
Width	2.20 in (5.6 cm)
Output Voltage	120 V 208 V
Depth	1.81 in (4.6 cm)
Product Weight	20.79 lb(US) (9.43 kg)
Mounting Location	Side
Mounting preference	No preference
Input Plug Type	NEMA L14-30P
Mounting Mode	Not rack-mountable
Rack units	0U
Mounting position	Vertical
Communication Port Protocol	SNMP Redfish
Line Rated Current	24 A
Input current limits	30 A
Load Capacity	4992 VA
Input Frequency	50/60 Hz

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>Outlet type and quantity</b>	16 NEMA 5-20R 7C13/C15 1C19/C21
<b>Communication Network Type</b>	10/100/1000BASE-T

## Environment

<b>Product Certifications</b>	cUL Listed FCC part 15 class A
<b>Standards</b>	UL 62368-1
<b>Ambient air temperature for operation</b>	23...140 °F (-5...60 °C)
<b>Relative Humidity</b>	5...95 %
<b>Operating altitude</b>	0...10000 ft
<b>Ambient Air Temperature for Storage</b>	-13...149 °F (-25...65 °C)
<b>Storage Relative Humidity</b>	5...95 %
<b>Storage altitude</b>	0...50000 ft (0.0000000000...15240.0000000000 m)

## Ordering and shipping details

<b>GTIN</b>	731304356356
-------------	--------------

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	80.35 in (204.1 cm)
<b>Package 1 Width</b>	4.69 in (11.92 cm)
<b>Package 1 Length</b>	6.48 in (16.47 cm)
<b>Package 1 Weight</b>	22.53 lb(US) (10.22 kg)

## Contractual warranty

<b>Warranty</b>	3 years repair or replace
-----------------	---------------------------



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) **3780**

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard **Yes**

Packaging without single use plastic **No**

[EU RoHS Directive](#) **Compliant with Exemptions**

SCIP Number **31346aed-552c-4a16-81d9-e683a383b6da**

REACH Regulation [REACH Declaration](#)

## Use Again

### Repack and remanufacture

Circularity Profile [End of Life Information](#)

Removable battery **Yes**

Take-back **No**

WEEE  **The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**

Image of product / Alternate images

Alternative

---

