

# Product data sheet

Specifications



## APC Step-Down Transformer RM 2U 208V IN 120V OUT; w/5-20 Receptacles

AP9626

### Overview

<b>Presentation</b>	The Step-Down Transformer converts high voltage (208 or 200 VAC) output into low voltage (120 or 100 VAC) output for powering low voltage AC equipment.
<b>Lead time</b>	Usually in Stock

### Main

<b>Main Input Voltage</b>	208 V
<b>Product or Component Type</b>	Accessory
<b>Main Output Voltage</b>	120 V
<b>Input Connection Type</b>	NEMA L6-30P
<b>Number of rack unit</b>	2U
<b>Number of cables</b>	1
<b>Provided Equipment</b>	User Manual Rack Mounting brackets

### Physical

<b>Color</b>	Black
<b>Height</b>	3.50 in (8.9 cm)
<b>Width</b>	17.52 in (44.5 cm)
<b>Depth</b>	24.02 in (61 cm)
<b>Product Weight</b>	95.20 lb(US) (43.18 kg)
<b>Mounting Location</b>	Front
<b>Mounting preference</b>	No preference
<b>Mounting Mode</b>	Rack-mounted

### Input

<b>Acceptable Input Voltage</b>	208 V
<b>Max line current</b>	24 A
<b>Input current limits</b>	30 A
<b>Load Capacity</b>	5000 VA

### Output

<b>Maximum Total Current Draw per Phase</b>	24 A
<b>Number of power socket outlets</b>	12

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

---

Efficiency	90 %
------------	------

---

Number of power socket outlets	12 NEMA 5-20R
--------------------------------	---------------

## Conformance

---

Product Certifications	CSA
------------------------	-----

---

Standards	OSHPD UL 1778
-----------	------------------

## Environmental

---

Ambient air temperature for operation	32...104 °F (0...40 °C)
---------------------------------------	-------------------------

---

Relative Humidity	0...95 %
-------------------	----------

---

Operating altitude	0...10000 ft
--------------------	--------------

---

Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
-------------------------------------	--------------------------

---

Storage Relative Humidity	0...95 %
---------------------------	----------

---

Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)
------------------	--

## Ordering and shipping details

---

GTIN	731304249139
------	--------------

## Packing Units

---

Unit Type of Package 1	PCE
------------------------	-----

---

Number of Units in Package 1	1
------------------------------	---

---

Package 1 Height	10.00 in (25.4 cm)
------------------	--------------------

---

Package 1 Width	37.52 in (95.3 cm)
-----------------	--------------------

---

Package 1 Length	24.49 in (62.2 cm)
------------------	--------------------

---

Package 1 Weight	110.2 lb(US) (50 kg)
------------------	----------------------

## Contractual warranty

---

Warranty	2 years repair or replace
----------	---------------------------

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) 4550

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant with Exemptions

REACH Regulation [REACH Declaration](#)

Halogen content performance Product contains halogen above thresholds

### Energy efficiency

Optimized Energy Efficiency Energy efficient product

## Use Again

### Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back Yes

Image of product / Alternate images

Alternative

---

