

# QUANTUM QR SERIES

## RESIDENTIAL BROWSER BASED TELEPHONE ENTRY SYSTEM

100-600 tenants, 300-3000 cards and 300-1000 codes

Remote programmable, Browser Based

Programming via LAN, WAN, Direct Connect or System's Keypad

No Dedicated IP needed

Backlit Keypad Intercom Mode, Automatic Call Forwarding

Brushed stainless steel, dark gray powder coated back box

Surface and Flush Mount / Indoor or Outdoor

24 months warranty



FEATURES/MODEL	QR4 Surface	QR4FF Full Flush	QR5 Surface	QR5FF Full Flush	QR5IP Surface	QR5IPFF Full Flush
Input power 12Vac included	12Vac/12Vdc	12Vac/12Vdc	12Vac/12Vdc	12Vac/12Vdc	12Vac/12Vdc	12Vac/12Vdc
Current consumption	900mA	1150mA	1150mA	1150mA	1150mA	1150mA
Operating temperature	10-145 °F	10-145 °F	10-145 °F	10-145 °F	10-145 °F	10-145 °F
Liquid Crystal Display	n/a	n/a	n/a	n/a	n/a	n/a
Tenant capacity	1	1	10	10	10	10
Code capacity	50	50	100	100	100	100
Card capacity	50	50	100	100	100	100
26-Bit Wiegand input	n/a	n/a	1, incl.reader	1, incl.reader	1, incl.reader	1, incl.reader
Auto Door Schedules	n/a	n/a	10	10	10	10
Time Zones	n/a	n/a	10	10	10	10
Holidays	n/a	n/a	20	20	20	20
Temp. cards/codes	n/a	n/a	10	10	10	10
Unlock hold cards/codes	n/a	n/a	10	10	10	10
Unlock hold timer	yes w/o timer	yes w/o timer	1-98 hours	1-98 hours	1-98 hours	1-98 hours
QWCM IP Module	n/a	n/a	optional	optional	yes	yes
Telephone line	analog	analog	analog	analog	analog	analog
Remote access	yes	yes	yes	yes	yes	yes
Dry contact relay	2	2	2	2	2	2
Door sensor	n/a	n/a	2	2	2	2
Auxiliary input	2	2	2	2	2	2
Event recording buffer	n/a	n/a	optional QWCM	optional QWCM	600	600
Slave access control	n/a	n/a	max. 8	max. 8	max. 8	max. 8
Dimension (HWD)	6-7/16" x 10-3/8" x 3-1/2" (SURFACE MOUNT)			9-13/16" x 11-13/16" x 3-5/8" (Flush mount) (TOTAL DIMENSION) 7-1/2" x 10-1/2" x 3-5/8" (inside Ring)		

### ACCESSORIES

**QVPC:** Analog color camera  
**USP1:** AC and Telephone surge protector  
**USP2L:** Surge and Lightning protection  
**UBAT1:** 12VDC 4.5 Ahr backup battery  
**IREXIT:** Infrared exit switch  
**AHP5:** Heater-pad

**USCR:** Satellite card reader  
**USKP:** Satellite keypad  
**USKPR:** Satellite reader/keypad combo  
**UCRM:** Satellite RS-485 controller  
**UWCR:** 26-Bit card reader  
**UFOB:** Keyfob

**UCLAM:** Clam shell card  
**UIISO:** ISO card  
**UPM1S:** 42" H Single arm pedestal  
**UPM2:** Dual vertical arm pedestal  
**UPM5:** Dual horizontal arm pedestal  
**UPM6L:** 64" H Single arm pedestal