AXIS Unified Power®
Integrated Power Systems

AXIS Unified Power Systems combine system power, lock power and distribution alongside AXIS™ A1210-B or A1610-B access hardware in one compact and secure UL Listed solution. Solutions are available from 2 to 8 doors, in single or dual voltage, standard or network managed.

Unified Power Features

- Single enclosure solution reduces wall space requirements
- Single AC drop
- Removable backplate for easy installation
- Predrilled & tapped holes for access panel mounting
- Mounting hardware included
- Single or dual voltage, standard or network managed

Need help selecting a product? Try our Product Selector and drag and drop
Configurator
!

DV: Dual Voltage (12 and 24V)

SV: Single Voltage (12 or 24V)



{jatabs type="content" position="top" width="900" heightTabs="30" height="1700" mousetype="click" animType="animMoveHor" skipAnim="false" duration=1000 }
[tab title="Products"] 2-4 Door Unified Type

Mo

DV Standard FPO75-B100C4D8E2X 2A/12V and 2A/24V
4 Lo

DV Managed	FPO75-B100M8NL4E2X	2A/12V and 2A/24V	8 Man

6-8 Door Unified	Type	Model	Power
DV Standard	FPO150-B100C8D8E4X	4A/12V and 4A/24V	8 L
DV Managed	FPO150-B100D8M8NL4E4X	4A/12V and 4A/24	8

AXIS Enclosures	Doors	Model	Dimens
2-4		E2X	20H x 16W x 4.5D
6-8		E4X	24H x 20W x 6.5D

[/tab] [tab title="More Information"]

Agency Listings

• UL294 / UL603 / UL1076 / ULC S319 • CSA C22.2 #107.1 •

FCC Part 15, Subpart B

• IEC 62368-1:2014, EN55032:2015, EN61000-3-2:2014

• EN6100-3-3:2013, EN55024:2010 +A1:2015

• CE, UKCA, BIS IS13252(Part1):2010, NOM 001:2018, RCM, SAA

• CSFM Approved, ROHS 3 Lead Free

2-4 Door Unified	Model	Datasheet	Manuals
	FPO75-B100C4D8S2X	DS	IM CAD AG
	FPO75-B100M8N4E2X	DS	IM CAD AG

6-8 Door Unified	Model	Datasheet	Manuals

FPO150-B100C8 E4X CAD AG
FPO150-B100D8 E4X CAD AG

AXIS Enclosures	Model	Datasheet	Manuals
E2X		DS	-	CAD	AG
E4X		DS	-	CAD	AG

[/tab] {/jatabs}