

Product data sheet

Specifications



APC NetShelter Switched Rack PDU, 1U, 1PH, 3.7kW 230V 16A or 3.3kW 208V 16A, 8 C13 outlets, C20 cord

AP7921B

Overview

Presentation This APC Switched Rack PDU power distribution unit has a wide range of standardized PDU features that increase network efficiency, manageability and functionality. The output and input connections are (8)C13. Network management capabilities allow you to configure and manage rack PDUs from remote locations. It has has a local current monitoring display that gives a visible warning in case of an overload. The remote individual outlet control provides real-time monitoring of connected loads. It has a multi-tier user access that enables you to restrict unauthorized use of outlets. This rack has a single input power source making it easy to install.

Lead time Usually in Stock

Main

Color Black

Product or Component Type PDU

PDU Type Switched

Cord length 8.2 ft (2.5 m)

Number of cables 1

Provided Equipment Installation guide
Rack Mounting brackets
User Manual

Complementary

Input Voltage 200 V
208 V
230 V

Height 1.73 in (4.4 cm)

Width 17.52 in (44.5 cm)

Output Voltage 208 V
230 V

Depth 4.25 in (10.8 cm)

Product Weight 5.004 lb(US) (2.27 kg)

Mounting Location Front
Rear

Mounting preference No preference

Input Plug Type IEC 60320 C20

Mounting Mode Rack-mounted

Rack units 1U

Mounting position Horizontal

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| | |
|--------------------------|-----------------|
| Line Rated Current | 16 A |
| Acceptable Input Voltage | 200...240 V |
| Input current limits | 20 A |
| Load Capacity | 3680 VA |
| Input Frequency | 50/60 Hz |
| Outlet type and quantity | 8 IEC 60320 C13 |

Environment

| | |
|---------------------------------------|--|
| Product Certifications | cUL Listed CE CSA GOST IRAM MIC UL Listed VDE VCCI |
| Standards | EN 55022 Class A EN 55024 EN 61000-3-2 EN 61000-3-3 UL 60950 |
| Ambient air temperature for operation | 32...113 °F (0...45 °C) |
| Relative Humidity | 0...95 % |
| Operating altitude | 0...10000 ft |
| Ambient Air Temperature for Storage | -13...149 °F (-25...65 °C) |
| Storage Relative Humidity | 0...95 % |
| Storage altitude | 0...50000 ft (0.0000000000...15240.0000000000 m) |

Ordering and shipping details

| | |
|-------------------|--------------|
| GTIN | 731304331629 |
| Country of origin | IN |

Packing Units

| | |
|------------------------------|-----------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 2.76 in (7 cm) |
| Package 1 Width | 13.50 in (34.3 cm) |
| Package 1 Length | 18.50 in (47 cm) |
| Package 1 Weight | 7.61 lb(US) (3.45 kg) |

Contractual warranty

| | |
|----------|---------------------------|
| Warranty | 2 years repair or replace |
|----------|---------------------------|



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) **916**

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard **Yes**

Packaging without single use plastic **No**

[EU RoHS Directive](#) **Compliant with Exemptions**

SCIP Number **1cdb2fed-a06f-4574-913d-8df8e70936b2**

REACH Regulation [REACH Declaration](#)

California proposition 65 **WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov**

Energy efficiency

Optimized Energy Efficiency **Energy efficient product**

Use Again

Repack and remanufacture

Circularity Profile [End of Life Information](#)

Removable battery **Yes**

Take-back **Yes**

Image of product / Alternate images

Alternative



