

PA-200

Piezo Chime



Piezo chime can be mounted in 1-1/4" hole on a single gang wall plate

Features

Standard Features

- Sound level 80 to 85 dB
- Chime mounts in 1-1/4" hole on single gang wall plate
- Chime can be flange mounted

Options

- Available pre-mounted on a single gang wall plate (**TS-43**)
- Single gang wall plate available for self-mounting (**RP-22E**)

Specifications

Dimensions

- Required mounting hole: 1-1/4"

Electrical

- Operates on 12 -24 VDC
- Current draw 95mA at 12 VDC, 140mA at 24 VDC
- 6" red, blue, and black leads

PA-300

Dual Tone Piezo Buzzer



Piezo buzzer with adjustable tone can be mounted in 3/4" hole on a single gang wall plate

Features

Standard Features

- Buzzer mounts
- Sound level 85db
- Continuous and slow pulse tone
- Buzzer mounts in 3/4" hole
- Bezel shaped case made of plastic

Options

- Wall plates available for self-mounting: slimline (**RP-23SLIMLINE**), narrow stile (**TS-34NPO**), or standard single gang (**RP-23**)

Specifications

Dimensions

- Required mounting hole: 3/4"

Electrical

- Operates on 3 to 24 VDC
- 6" red, yellow, and black leads