

## Cat5e 350 MHz Solid Core (UTP) PVC Bulk Ethernet Cable - Black, 1000 ft. (304.8 m), TAA

MODEL NUMBER: N022-01K-BK



Premium cabling designed for Cat5/5e premise (in-wall) applications, such as connecting an Ethernet wall jack to a router, patch panel or switch.

### Features

#### Perfect Solution for Cat5/5e Premise Applications

- Designed for fast transmission and excellent signal quality throughout your LAN
- Delivers speeds up to 350 MHz/1 Gbps
- Ideal for all non-plenum horizontal wiring applications, including 10/100/1000 Base-T Ethernet, 100 Mbps TPDDI, 155 Mbps ATM, ISDN, voice and Token Ring Type 3 applications

#### Premium Construction for Superior Performance

- Made from 24 AWG copper wire
- 4-pair solid UTP
- CMR-rated PVC jacket
- Meets most current industry standards, including IEEE 802.3ab, IEEE 802.5, ANSI/EIA/TIA 568, ISO/IEC 11801 and ETL (category 5e, draft 11)

#### TAA-Compliant

- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

## Specifications

| OVERVIEW    |              |
|-------------|--------------|
| UPC Code    | 037332144195 |
| Technology  | Cat5/5e      |
| CONNECTIONS |              |

### Highlights

- Ideal for all non-plenum horizontal wiring applications
- Rated for 350 MHz/1 Gbps communications
- High-quality 24 AWG 4-pair solid copper wire
- CMR-rated PVC jacket
- Meets IEEE 802.3ab and ANSI/EIA/TIA 568 standards

### Package Includes

- N022-01K-BK Cat5e 350 MHz Bulk Solid-Core PVC Cable, Black, 1000 ft.



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                      |                             |
|--------------------------------------|-----------------------------|
| Side A - Connector 1                 | BARE WIRE                   |
| Side B - Connector 1                 | BARE WIRE                   |
| Crossover Wiring                     | No                          |
| Connector Type                       | Bare Wire                   |
| Angled Connector                     | No                          |
| <b>PHYSICAL</b>                      |                             |
| Cable Jacket Color                   | Black                       |
| Cable Jacket Material                | PVC                         |
| Cable Jacket Rating                  | CMR                         |
| Cable Shielding                      | UTP                         |
| Cable Outer Diameter (OD)            | 5.1 mm                      |
| Number of Conductors                 | 4 Pair                      |
| Conductor Material                   | Solid Copper                |
| Conductor Gauge                      | 24 AWG                      |
| Cable Length (ft.)                   | 1000                        |
| Cable Length (m)                     | 304.88                      |
| Cable Length (in.)                   | 12000                       |
| Cable Length (cm)                    | 30480                       |
| Shipping Dimensions (hwd / in.)      | 10.63 x 13.78 x 13.78       |
| Shipping Dimensions (hwd / cm)       | 27.00 x 35.00 x 35.00       |
| Shipping Weight (lbs.)               | 21.15                       |
| Shipping Weight (kg)                 | 9.59                        |
| <b>ENVIRONMENTAL</b>                 |                             |
| Operating Temperature Range          | -4° to 167°F (-20° to 75°C) |
| Storage Temperature Range            | 32° to 140°F (0° to 60°C)   |
| <b>COMMUNICATIONS</b>                |                             |
| Bandwidth per TIA Standard           | 100 MHz                     |
| Maximum Bandwidth as Tested          | 350 MHz                     |
| Network Compatibility                | 1 Gbps (Gigabit)            |
| IEEE Standards Supported             | 802.3ab                     |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                             |
| Antibacterial                        | No                          |
| IP68 Rated                           | No                          |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                     |                                                                  |
|-------------------------------------|------------------------------------------------------------------|
| Snagless Connector                  | No                                                               |
| STANDARDS & COMPLIANCE              |                                                                  |
| Product Compliance                  | RoHS; IEEE 802.3ab 1000Base-T; REACH; Trade Agreements Act (TAA) |
| WARRANTY & SUPPORT                  |                                                                  |
| Product Warranty Period (Worldwide) | Lifetime limited warranty                                        |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.