



2-Port Outdoor Vandalproof Gigabit PoE++ Extender

IEEE 802.3bt (4PPoE) Compliant with 95 W Power Input, Two 30 W Output Ports, Extends PoE up to 100 m (328 ft.), 60 W PoE Power Budget, IP67 Waterproof, IK10-rated, Metal Housing

Part No.: **561648**

EAN-13: 0766623561648 | UPC: 766623561648

This PoE++ Extender / Repeater doubles the range of two Gigabit Power over Ethernet connections - even in harsh outdoor conditions

The Intellinet Network Solutions 2-Port Outdoor Vandalproof Gigabit Ultra PoE Extender adds up to 100 m (328 ft.) to the connection distance from a PoE source to one or two output devices via Cat5e or Cat6 cable. This PoE++ (4PPoE) extender does not need an additional power supply since it draws its power from the PoE input.

Designed for Outdoor Use

This PoE++ extender is the right power and data connector for its suitability to a wide variety of environments. Its weatherproof IP67 (waterproof and dustproof) rating, vast operating temperature range of -20 – 60°C (-4 – 140°F) and vandal-proof IK10 score make the Intellinet Network Solutions 2-Port Outdoor Vandalproof Gigabit Ultra PoE Extender able to withstand harsh conditions.

Reduced Wiring Costs

This Ultra PoE Extender helps avoid the expense of running AC power lines for a wireless access point, network camera, IP phone, or other compatible device. Simply connect the PoE Extender to the LAN switch port through existing Cat5e/6/6a cables to deliver DC power as well as transfer data.

Power over Ethernet 802.3bt Compliant with up to 95 W input

This Ultra PoE Extender supports the IEEE 802.3bt protocol over four pairs (4PPoE), which allows for a power input of 95 W. It forwards data at Gigabit speeds and offers up to 30 watts per port to a connected IEEE 802.3at- or IEEE 802.3af-compliant device. The cable length on both ends can be up to 100 meters (328 ft.), bringing the total distance between PoE source and device to 200 m (656 ft.).

Simple Installation

This PoE Extender was designed to be as easy as possible to set up and use. All it takes to have it up and running is to connect its **PoE In** port to your PoE injector or PoE switch and to connect the **PoE Out** ports to the PoE devices you want to connect (e.g., a VoIP phone and a PoE network camera).

Features:

- Doubles the maximum connection distance between PoE source and device from 100 m (328 ft.) to 200 m (656 ft.)
- Connects and powers two PoE devices, such as network cameras, wireless access points or VoIP phones, from a PSE port on a PoE injector or PoE switch
- Delivers up to 60 W to two connected PoE devices with per-port power up to 30 W
- Supports up to 95 W power input from a PoE injector or switch
- IP67-rated, dustproof and waterproof
- IK10-rated, vandal-proof
- Supports 10/100/1000 Mbps data rates
- Total PoE power budget of 60 watts
- Saves time and money by delivering data and power via existing network cables
- Requires no additional power supply; draws power directly from the PoE input
- PoE awareness to ensure that power is only sent to IEEE 802.3at/af-compliant devices; non-PoE devices only receive data
- Short-circuit, overload and high-voltage protection
- Grounding point to protect equipment from external electrical surges
- Port surge protection up to 6 kV
- Compatible with IEEE 802.3bt/at/af-compliant PoE injectors and PoE switches (PSE)
- Compatible with IEEE 802.3at/af-compliant powered devices (PD)
- Functional as a PoE-powered 3-port Gigabit switch with PoE passthrough

For more information on Intellinet products, consult your local dealer or visit www.intellinet-network.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Switch fabric of 6 Gbps
- Supports jumbo frames up to 9 kBytes
- Supports 2048 MAC address entries
- Mounting holes for wall mounting
- Earthing kit included
- Three-year warranty

Specifications:

Standards

- IEEE 802.3af (Power over Ethernet)
- IEEE 802.3at (High-Power PoE+ Power over Ethernet)
- IEEE 802.3bt (Ultra PoE++/4PPoE Power over Ethernet)
- IEEE 802.3i (10Base-T Ethernet)
- IEEE 802.3ab (Gigabit Ethernet)
- IEEE 802.3x (Full duplex and flow control)
- IEEE 802.3u (100Base-TX Fast Ethernet)

General

- Media support:
 - 10Base-T Cat5e UTP/STP RJ45, 8 pin
 - 100Base-TX Cat5e UTP/STP RJ45, 8 pin
 - 1000Base-T Cat5e UTP/STP RJ45, 8 pin
- Ports:
 - One RJ45 10/100/1000 Mbps input port
 - Two RJ45 10/100/1000 Mbps PoE output ports
- MAC address table: 2048 entries
- Buffer memory: 256 kB
- Backplane speed: 6 Gbps
- Switch architecture: store and forward
- Certifications: FCC Class A, CE, RoHS

PoE Pinout

- Pin 1: DC (+)
- Pin 2: DC (+)
- Pin 3: DC (-)
- Pin 6: DC (-)

Power

- Max PD output power: 30 W per port, 44 - 55 VDC
- Input power: IEEE 802.3bt/at/af compliant PSE, 95 W max., 44 - 57 VDC

Physical

- IEC ratings: IP67 (weatherproof) and IK10 (vandalproof metal housing)
- Dimensions (L x W x H): 150 x 73 x 44 mm (5.9 x 2.87 x 1.73 in.)
- Suitable network cable diameter: 5.5 mm max.
- Weight: 353 g (0.78 lbs.)

- Operating temperature: -20 - 60°C (-4 - 140°F)
- Storage temperature: -40 - 80°C (-40 - 176°F)
- Operating humidity: 10 - 90% RH, non-condensing
- Storage humidity: 5 - 90% RH, non-condensing

Package Contents

- 2-Port Outdoor Vandalproof Gigabit PoE++ Extender
- Earthing kit
- Three IP67-rated cable glands
- Instructions



For more information on IntelNet products, consult your local dealer or visit www.intellinet-network.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

