Specifications

Eaton EMI201-10



Catalog Number: EMI201-10

Eaton Metered Input rack PDU, 0U, L14-30P input, 5.76 kW max, 120/240V, 24A, 10 ft cord, Split-phase, Outlets: (24) 5-20R

General specifications

Product Name	**Catalog Number**
Eaton metered input PDU	EMI201-10
UPC	**Product Length/Depth**
786685974767	63.1 in
Product Height	**Product Width**
2.05 in	2.1 in
Product Weight	**Warranty**
11.5 lb	3 year
Compliances	**Certifications**
Contact Manufacturer	UL Listed

Powering Business Worldwide

Product specifications

Form factor
0U (Vertical)

Outlet control
No

Phase
Split-phase

Wattage
5.76 kW max

Amperage Rating
24A

Input voltage
120/240V

Input connection
L14-30P

Outlets
(24) 5-20R

Cord length
10 ft

Frequency rating
50-60 Hz

Ethernet interface
Yes

Serial interface
RS-232

Operating Temperature
0° to 60°C (32° to 140°F)

Resources

Certification reports
Eaton RoHS Declaration of Conformity: ePDU G3

Drawings
Eaton ePDU G3 Metered Input EMI201-10 technical drawing

Eaton PDU EMI201-10 technical drawing

Manuals and user guides
Eaton ePDU G3 EMP installation and connection quick start guide

Eaton ePDU G3 operations manual

Eaton ePDU G3 installation and connectivity quick start guide

Eaton ePDU G3 instruction set - system objects

Service and troubleshooting
EMI201-10 eNMC replacement configuration file

Specifications and datasheets
Eaton Specification Sheet - EMI201-10



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia