

# Product data sheet

Specifications

## APC IT Power Distribution Module 3 Pole 4 Wire 50A CS50 980cm



PDM3450CS50-980

### Overview

Presentation	Factory assembled and tested Power Distribution Modules include circuit breaker, power cord, power connection, and circuit monitoring. Auto-detection of modules by the Modular PDU minimizes installation time.
Lead time	Usually Ships within 3 Weeks

### Main

Main Input Voltage	208 V 3 phase
Main Output Voltage	208 V 3 phase
Output connector type	CS50 1
Provided Equipment	Installation guide

### Physical

Color	Black
Height	5.0000000000 in (12.7 cm)
Width	17.5 in (44.5 cm)
Depth	16.0 in (40.6 cm)
Net Weight	13.43 lb(US) (6.09 kg)

### Input

Input Frequency	60 Hz
Permissible voltage	200...240 V
Max line current	50 A

### Output

Maximum Total Current Draw per Phase	50 A
Number of power socket outlets	1 CS50

### Conformance

Product Certifications	UL Listed
------------------------	-----------

### Ordering and shipping details

GTIN	731304281641
------	--------------

### Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	5.0000000000 in (12.7 cm)
<b>Package 1 Width</b>	16.0 in (40.6 cm)
<b>Package 1 Length</b>	17.5 in (44.5 cm)
<b>Package 1 Weight</b>	14.64 lb(US) (6.64 kg)

## Contractual warranty

<b>Warranty</b>	1 year repair or replace
-----------------	--------------------------

## Sustainability

**Green Premium™** label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

[Learn more about Green Premium >](#)



Take-back   Transparency

## Resource performance

✔ Take-Back Program Available

---

## Well-being performance

✔ Mercury Free

---

**Reach Regulation**

[REACH Declaration](#)

---

**Eu Rohs Directive**

Under investigation

---

**Environmental Disclosure**

[Product Environmental Profile](#)

---

**Circularity Profile**

[End of Life Information](#)

---