Specifications



Eaton EMA114-10

Eaton Managed PDU, 1PH, 0U, L5-20P input, 10 ft cord, 1.92kW, 16A, 120V, 24 Outlets (24) 5-20R, TAA

General specifications	
PRODUCT NAME	Eaton managed PDU
CATALOG NUMBER	EMA114-10
UPC	743172078919
PRODUCT LENGTH/DEPTH	66.5 in
PRODUCT HEIGHT	2.09 in
PRODUCT WIDTH	2.05 in
PRODUCT WEIGHT	15.9 lb
WARRANTY	3 year
COMPLIANCES	RoHS Compliant TAA Compliant
CERTIFICATIONS	UL Listed

Powering Business Worldwide

Product specifications

FORM FACTOR	0U (Vertical)
OUTLET CONTROL	Yes
PHASE	Single-phase
WATTAGE	1.92 kW max
AMPERAGE RATING	16A
INPUT VOLTAGE	120V
INPUT CONNECTION	5-20P, L5-20P
OUTLETS	(24) 5-20R
CORD LENGTH	10 ft
FREQUENCY RATING	50-60 Hz
SERIAL INTERFACE	RS-232
OPERATING TEMPERATURE	0° to 60°C (32° to 140°F)

Resources

CERTIFICATION REPORTS	Eaton ePDU certificate of volatility Eaton RoHS Declaration of Conformity: ePDU G3
DRAWINGS	Eaton ePDU Managed eMA114-10 technical drawing Eaton Advanced Monitored and Managed ePDU visio stencil
MANUALS AND USER GUIDES	Eaton ePDU G3 instruction set - system objects Eaton ePDU G3 replace and configure eNMC module Eaton ePDU G3 1U and 2U installation addendum Eaton ePDU G3 operations manual Eaton Double-wide G3 ePDU installation and connectivity quick start guide
SERVICE AND TROUBLESHOOTING	EMA114-10 eNMC replacement configuration file
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - EMA114-10

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

© 2025 Eaton. All Rights Reserved.