

Product data sheet

Specifications



APC IT Power Distribution Module 3x1 Pole 3 Wire 20A 240V IEC309 1680cm 1680cm 1680cm



PDM1320IEC-3P-3

Overview

Presentation Factory assembled and tested Power Distribution Modules include circuit breaker, power cord, power connection, and circuit monitoring. Auto-detection of modules by the Modular PDU minimizes installation time.

Lead time Usually Ships within 3 Weeks

Main

Main Input Voltage 240 V

Main Output Voltage 240 V

Provided Equipment Installation guide

Physical

Color Gray

Height 6.0 in (15.2 cm)

Width 17.008 in (43.2 cm)

Depth 16.5 in (41.9 cm)

Net Weight 20.04 lb(US) (9.09 kg)

Input

Input Frequency 60 Hz

Max line current 20 A

Output

Maximum Total Current Draw per Phase 20 A

Number of power socket outlets 3 IEC 309 20 A

Conformance

Product Certifications UL Listed

Ordering and shipping details

GTIN 731304268192

Packing Units

Unit Type of Package 1 PCE

Number of Units in Package 1 1

Package 1 Height	6.0 in (15.2 cm)
Package 1 Width	16.5 in (41.9 cm)
Package 1 Length	17.008 in (43.2 cm)
Package 1 Weight	22.05 lb(US) (10 kg)

Contractual warranty

Warranty	1 year repair or replace
-----------------	--------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)





Take-back Transparency RoHS/REACH

Resource performance

 Take-Back Program Available

Well-being performance

 Mercury Free

 RoHS Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)
