**inSIGHT™ Data Com Rack Power Distribution Unit**

## Intelligent Power Distribution

# Complete line of single and three phase intelligent PDUs

HUBBELL

### Features

- Includes Advanced Monitoring on LCD screen and web browser
- Locking standard cords to prevent inadvertent disconnection
- Up to four environmental sensors per PDU that measures temperature and humidity
- Monitored and switch enabled - Use Switching cords for equipment switching capability.
- Available in Black, Blue, Red, and White

### Ordering Information

| Type | Nominal | Catalog Number | UPC |
|---|---|---|---|
| Switch Ready | 208V Three Phase | **PV72ID50GE-10BL** | 662620366036 |

### Listings

UL 2416
EIA 310-E Universal Mounting Pattern
UL 60950-1
SNMP V3

### Specifications

| | |
|---|---|
| Input Current (A) | 50 Amp |
| Input Power Cord | CS8365C Plug |
| Receptacle group | 24 C13 & 12 C19 Receptacle |
| PDU Size | 72" vertical mount |
| Regulatory Approval | TUV Certified to UL / CSA 609050-1 |
| Operating Environment | 0 to 60 |
| Storage Environment | -25 to 65 |
| PDU Dimension (inches) | 72 length X 2.2 width X 4.8 depth |
| Network Interface | Dual Ethernet RJ-45, 10/100 Mbit/sec |

### Performance

**Intelligence**

Remote & touch screen display

**Low profile**

2.18" X 2". Improves airflow

**Receptacle Locking**

Prevents inadvertent disconnections. Secured with standard cords

**Touch and Rotate Digital Display**

Touch to view / rotate. Optional sensor -daisy chain up to four for temp/humidity

### Accessories

| | |
|---|---|
| One Sensor (A) and 6 foot connecting cord | **PENVPODA** |
| Two Sensors (A, B) and two 6 foot connecting cord | **PENVPODAB** |
| Three Sensors (A, B, C) and three 6 foot connecting cords | **PENVPODABC** |
| Four sensors (A, B, C, D) and four 6 foot connecting cords | **PENVPODABCD** |
| Environmental sensor 6 foot connecting cord | **PENV6FTCORD** |
| Environmental sensor 9 foot connecting cord | **PENV9FOOTCORD** |
| Outlet Switching and Metering, C13-C14, 5 foot | **PSWCRDC1314-05** |
| Outlet Switching & Metering, C19-C20, 5 foot | **PSWCRDC1920-05** |

### Online Resources

eCatalog



HUBBELL®
Hubbell Premise Wiring