Product data sheet

Specifications



APC Rack PDU 9000 Switched, ZeroU, 17.3kW, 208V, (20) C13/ C15, (12) C19/C21

APDU9966

Overview

Lead time	Usually in Stock

Main

Color	Black
Product or Component Type	PDU
PDU Type	Switched
Cord length	6 ft (1.8 m)
Number of cables	1
Provided Equipment	Installation guide Rack Mounting brackets Safety guide

Complementary

Input Voltage	208 V 3 phase
Height	72.17 in (183.3 cm)
Width	4.37 in (11.1 cm)
Output Voltage	208 V
Depth	2.99 in (7.6 cm)
Product Weight	30.9 lb(US) (14 kg)
Mounting Location	Side
Mounting preference	No preference
Input Plug Type	IEC 60309 60 A 3P+PE
Mounting Mode	Rack-mounted
Communication Port Protocol	SNMP Redfish
Line Rated Current	48 A
Max line current	48 A
Input current limits	60 A
Load Capacity	17300 VA
Input Frequency	50/60 Hz
Outlet type and quantity	20C13/C15 12C19/C21
Communication Network Type	10/100/1000BASE-T

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

Product Certifications	cUL Listed FCC part 15 class A
Standards	IEC 62368-1
Ambient air temperature for operation	23…140 °F (-5…60 °C)
Relative Humidity	5…95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13…149 °F (-25…65 °C)
Storage Relative Humidity	5…95 %
Storage altitude	0…50000 ft (0.0000000000…15240.0000000000 m)

Ordering and shipping details

GTIN	731304356332

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	84.61 in (214.9 cm)
Package 1 Width	4.41 in (11.2 cm)
Package 1 Length	8.70 in (22.1 cm)
Package 1 Weight	44.004 lb(US) (19.96 kg)

Contractual warranty

Warranty	3 years repair or replace

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle)	**5641**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
EU RoHS Directive	**Compliant with Exemptions**
SCIP Number	**31346aed-552c-4a16-81d9-e683a383b6da**
REACh Regulation	**REACh Declaration**

Use Again

Repack and remanufacture

Circularity Profile	**End of Life Information**
Removable battery	**Yes**
Take-back	**No**
WEEE	 **The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**

Image of product / Alternate images

Alternative



