



ZvPro820-NA



ZvPro820-NA is a HD video encoder/QAM modulator with 2 HDMI inputs up to 1080i/1080p with embedded digital audio or analog audio. MPEG-2 QAM RF output. 1 delay match analog audio output for analog audio input. Closed Captions supported via composite. Includes power supply. Cables and Rack Kit sold separately

FEATURES

- RF Modulation
- Two HDMI inputs
- 1080p
- MPEG2 QAM RF output



kramer

TECHNICAL SPECIFICATIONS

General	<p>Power 100–240 VAC 50/60 Hz, 60W max. 30W Typical IEC 60320–C14</p> <p>Compliance FCC Class A, IEC60065, EN61000 (see manual 70–00031–00), CE, RoHS, RCM C–Tick</p> <p>Mounting The rack ears are sold separately and are not attached</p> <p>Cooling Dual internal cooling fans, Front inlet, Rear exhaust MBTF: 62,000 hours</p> <p>Enclosure Dimensions 8 in. (H) x 10 in. (W) x 1.75 in. (H) 20.32 cm (H) x 25.4 cm (W) x 4.445 cm (H)</p> <p>Carton Dimensions (individual) 2.75 in. (H) 14 in. x (W) 12 in. (D) 6.985 cm (H) 35.56 cm (W) x 30.48 cm (D)</p> <p>Temperature/Humidity Operating +32 F0 to +113 F0 (0 C0 to +45 C0) / 10% to 80%, non–condensing</p> <p>Enclosure Type Metal Shipping Weight: 5 lbs. (2.3 kg)</p> <p>Warranty 5 Years</p> <p>Vibration NSTA 1A in carton</p>
Inputs	<p>Component Video via RCA R/B/G Hydra cable, Din–to–Mini–Din DirecTV H25 cable, or VGA cable</p> <p>Stereo Analog and Digital Audio x2</p> <p>VGA Resolutions Supported 640x480, 720x480, 800x600, 1024x768, 1152x864, 1176x664, 1280x720, 1280x768, 1280x800, 1280x960, 1280x1024, 1360x768, 1440x900 at 60 70, 72, 75, 85 Hz. 1680x1050 and 1920x1080 at 60 Hz. VGA resolutions are broadcast centered in the best vertical fit into 1920x1080p30 or 1280x720p60</p> <p>Enclosure Dimensions 8 in. (H) x 10 in. (W) x 1.75 in. (H) 20.32 cm (H) x 25.4 cm (W) x 4.445 cm (H)</p> <p>Closed Caption EIA/CEA–608 captions accepted over composite video input</p> <p>ZvShow Extra digital channel, MPEG2 program stream file, up to 200 MB</p> <p>Line level input per channel via RCA connectors, Mini–Din, or 3.5mm analog audio pigtail with VGA cable. Digital SPDIF audio input via orange RCA connector</p>
Video Encoder	<p>Encoder Video Profile MPEG2 HD: ISO13818–2 MainProfile@ HighLevel</p> <p>Average Encoding Data Rate 18 Mbs per channel</p> <p>Encoder Audio Profile ATSC A/52, (AC–3)</p> <p>GOP Size 16</p> <p>Traffic Shaping Variable Bit Rate</p> <p>Encoding Latency Programmable 200 msec to 400 msec</p> <p>Video, Audio PID Programmable starting value</p> <p>Video Encoding Data Rates Variable, 10 Mbs – 24 Mbs per channel</p> <p>Color Profile 4:2:0</p> <p>Program Information Programmable program name, EIT</p>

Modulator/Upverter	<p>Modulation Types QAM 256 and 64 (ITU-T J83 Annex B) Interleaving modes: (64,2) only</p> <p>Output Power +45 dBmV typical</p> <p>I/Q Amplitude Imbalance < 1% typical</p> <p>Cable Standard HRC, IRC or STD</p> <p>Output Level Adjust 25 – 45 dBmV in 1dBmV steps</p> <p>Frequency Range Single or one paired, frequency agile QAM RF CATV channels 2–135 • 2kHz resolution • +/- 30 ppm accuracy</p> <p>MER > 38 dB typical</p>
Network Interface	<p>10/100 Mb Ethernet via RJ45 connection. IP address via DHCP (default) or static. Built-in web interface for easy configuration. All settings saved in NV storage</p>
Front Panel Color Display	<p>Lets users quickly obtain status at a glance, basic configurations, software revisions, and do updates</p>