



## Receiver for 1080p 4-Port HDMI Extending Splitter Transmitter

Receives One Input Signal from Transmitter up to 50 m (165 ft.),  
Single Ethernet Cable per Receiver, use with 207829, Black

Part No.: [207836](#)

EAN-13: 0766623207836 | UPC: 766623207836

---

Easily connect and extend HDMI display to a single source.

The Manhattan Receiver for 1080p 4-Port HDMI Extending Splitter Transmitter receives a signal from the Manhattan 1080p 4-Port HDMI Extending Splitter Transmitter. The powered receiver supports a reliable 1080p resolution video and multichannel audio transmission over longer distances than is possible with HDMI cables.

### Flexible Solution for Many A/V Applications

Ideal for trade shows, classrooms, home theater, conference rooms, business office and retail applications, the Manhattan Receiver for 1080p 4-Port HDMI Extending Splitter Transmitter, when paired with the Transmitting Unit, offers convenient display or projector placement. Cat6 Ethernet cabling — UTP, SSTP or SFTP (cables not included) — is less expensive and easier to install than HDMI cabling and in-line signal repeaters.

### Best Possible Image Quality

The Manhattan Receiver for 1080p 4-Port HDMI Extending Splitter Transmitter is HDMI and HDCP 1.4a compliant and delivers a stunningly clean, crisp and vivid picture up to 1080p resolution on four displays thanks to an integrated video

bandwidth amplifier. Additionally, it supports HD-quality 3D video, as well as LPCM, DTS and Dolby TrueHD audio.

## Features:

- This receiving (RX) unit requires the transmitting (TX) unit (207829)
- Receives a High-Definition (HD) digital audio/video signal from a 1080p 4-Port HDMI Extending Splitter Transmitter (connects up to four HD HDMI displays); distances up to 50 m (165 ft.) over Ethernet cable
- Supports 1080p resolution as well as HD 3D video and Deep Color (24-bits/pixel)
- 1080p resolution, 3D, Deep Color
- Fully HDCP compliant
- AC powered with Plug and Play installation; no special setup or remote required
- Plug-and-play installation
- Gold-plated contacts for corrosion-free connections
- Three-year warranty

## Specifications:

### Standards and Certifications

- HDCP 1.4a
- CE
- FCC
- RoHS2

### General

- Source-to-splitter (TX) range: up to 15 m (49 ft.)
- Cat6 cable 1080p at 50 m (165 ft.)
- Cat6 cable 720p at 60 m (200 ft.)
- Cat6 cable 480p at 80 m (264 ft.)
- Receiver(RX)-to-display range: up to 15 m (49 ft.)
- Power: 12 VDC @ 1 A ; AC power adapter, 0.9 m (2.9 ft.)
- LED power/status indicator
- Wallmountable
- Power: 12 VDC

### Connections

#### Transmitter (sold separately)

- One HDMI female, 19-pin (input)
- Four Ethernet female, RJ45 (output)
- One 5 VDC female, power (input)

#### Receiver

- One HDMI female, 19-pin (output)

- One Ethernet female, RJ45 (input)
- One 5 VDC female, power (input)

#### Signal Input/Output

- Input video signal: 400 – 600 mV
- Input DDC signal: 5 V p-p (TTL)
- Maximum single-link range: 1.65 Gbps and 1080p resolution
- Output video: HDMI 1.3, HDCP 1.4a
- Frequency: 1.65 Gbps / 165 MHz

#### Video Resolutions

- DTV/HDTV: 480i/480p/576i/576p/720p/1080i/1080p

#### Physical

- LED indicators: power and port connection
- Power adapter: 12 VDC / 2 A; 0.9 m (2.9 ft.)
- Power switch
- Dimensions: 100 x 65 x 25 mm (3.9 x 2.5 x 1 in.)
- Weight: 0.12 kg (0.26 lbs.)
- Housing: metal

#### Operating Environment

- Operation Temperature: 0 – 40°C (32 – 104°F)
- Storage Temperature: -20 – 60°C (-4 – 140°F)
- Humidity (noncondensing): 0 – 96%

#### Package Contents

- Receiver for 1080p 4-Port HDMI Extending Splitter Transmitter
- Power adapter
- Wallmounting brackets
- Quick Instruction Guide



