

Product data sheet

Specifications



Rack PDU, Basic, Zero U, 20A, 120V, (24)5-20

AP7530

Product availability: Stock - Normally stocked in distribution facility

Overview

Lead time Usually in Stock

Main

Color Black

Product or Component Type PDU

PDU Type Basic

Cord length 10 ft (3.05 m)

Number of cables 1

Provided Equipment
Cord retention bracket(s)
Installation guide
Rack Mounting brackets
Toolless Mounting Kit
User Manual

Complementary

Input Voltage
100 V
120 V

Height 63.74 in (161.9 cm)

Width 2.20 in (5.6 cm)

Output Voltage 120 V

Depth 1.73 in (4.4 cm)

Product Weight 10.71 lb(US) (4.86 kg)

Mounting Location Side

Mounting preference No preference

Input Plug Type NEMA L5-20P

Mounting Mode Rack-mounted

Rack units 0U

Mounting position Vertical

Line Rated Current 16 A

Acceptable Input Voltage 100...120 V

Input current limits 20 A

Load Capacity 1920 VA

Input Frequency 50/60 Hz

Outlet type and quantity 24 NEMA 5-20R

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Environment

Product Certifications	cUL Listed UL Listed
Standards	CSA C22.2 No. 60950-1-03 UL 60950-1
Ambient air temperature for operation	23...113 °F (-5...45 °C)
Relative Humidity	5...95 %
Operating altitude	0...15000 ft
Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
Storage Relative Humidity	5...95 %
Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)

Ordering and shipping details

Category	11309-APC RESALE PRODUCTS
Discount Schedule	APC1
GTIN	731304207962
Returnability	No
Country of origin	IN

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	84.02 in (213.4 cm)
Package 1 Width	5.00 in (12.7 cm)
Package 1 Length	5.98 in (15.2 cm)
Package 1 Weight	12.72 lb(US) (5.77 kg)
SCC14	731304207962

Contractual warranty

Warranty	2 years repair or replace
-----------------	---------------------------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) 120

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant

REACH Regulation [REACH Declaration](#)

Halogen content performance Product contains halogen above thresholds

Energy efficiency

Optimized Energy Efficiency Energy efficient product

Use Again

Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back Yes