

HIKVISION

DS-K3B601-R-MPg-Dp75: Turnstile

General Information/Key Features

- UNSPSC: 31162506
- Harmonization Code: 8529904900
- Country of Origin: US
- Automatic Alarm
- 12 Pairs of IR Light Detectors

Related Pages (Right click to open in new tab)

Shop Now. Visit the [DS-K3B601-R-MPg-Dp75](#) product page for detailed information

View [other Hikvision Turnstiles](#)

View over 1300 [video surveillance products from Hikvision](#)

Scroll down to view the Hikvision DS-K3B601-R-MPg-Dp75 specification sheet



HIKVISION
DS-K3B601-R-MPg-Dp75

<https://www.surveillance-video.com> is a distributor/reseller of over 120,000 security products from over 100 brands.

For over 45 years, we have earned the confidence of our customers by providing professional service and support.

If you need technical support or assistance to install your security system or any other products purchased from Surveillance-video.com, you can call us @ **800-955-5201** at any time.

DS-K3B601-x

Swing Barrier



The DS-K3B601-x series swing barrier with 12 pairs of IR lights is designed to detect unauthorized entrances and exits. In coordination with the access control system, a person can authenticate and pass through the lane by swiping their ID card or showing their face (integrated with the DS-K5603-Z).

The swing barrier is widely used at stadiums, construction sites, residences, etc.

Available Models:

DS-K3B601-L
DS-K3B601-M
DS-K3B601-R

- Brushless DC Electric Motor Supports More than 3,000,000 Barrier Open and Close Motions
- 12 Pairs of IR Light Detectors
- Customizable Audio Prompts
- Audible and Visual Nipping Alarm
- Anti-Force Locking Mechanism
- Self-Detection, Self-Diagnostics, and Automatic Alarm
- Audible and Visual Alarms, Including Intrusion Alarm, Reverse Passing Alarm, Tailgating Alarm, and Barrier Climbing Alarm
- Management via Remote Control and iVMS-4200 Control Client

Specifications

	DS-K3B601-L DS-K3B601-M DS-K3B601-R
System Parameters	
Communication Interface	TCP/IP, I/O, RS-232, RS-485
IR Light Detectors	12 pairs
Throughput	30 to 60 persons per minute
MCBF	>3,000,000 times
Lane Width Options	25.59" (650 mm), 29.53" (750 mm), 35.43" (900 mm), 43.31" (1100 mm)
Barrier Metal	Stainless steel; acrylic glass (optional)
Pedestal Metal	AISI304 stainless steel with the thickness 0.06" (1.5 mm)
Dimensions (L x W x H) per Pedestal	Without packaging: 59.06" x 7.87" x 38.98" (1500 mm x 200 mm x 990 mm) With packaging: 63.39" x 11.81" x 43.31" (1610 mm x 300 mm x 1100 mm)
Weight per Pedestal	With packaging: 242 lbs (110 kg)
Power Supply	100 to 240 VAC; 50 to 60 Hz
Power Consumption	320 W per lane
Working Temperature	-13° F to 158° F (-25° C to 70° C)
Working Humidity	10% to 90% (non-condensing)

Dimensions

Note: this diagram reflects a 650 mm lane width

