



TAK-4208 Telephone Auto Dialer and Announcer Unit (8-Input)



ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The Telephone Auto Dialer Unit unit(s) shall be Alpha Communications® / Cornell model **TAK-4208**, or approved equal. The **TAK-4208** shall be used in conjunction with an Alpha Communications® Emergency-Call (or similar) notification system, for up to eight (8) inputs.

The **TAK-4208** shall be a fully programmable auto dialer and digital announcer, designed for message notification. Once a contact input is detected, the **TAK-4208** shall dial up to eight (8) phone numbers and play a prerecorded message of up to one (1) minute in length.

Low voltage wiring shall be used and positive screw terminal and plug-in connectors shall be provided for installation wiring. The **TAK-4208** shall be mountable right to the surface of the wall or in a customer-supplied junction box cabinet, and shall require a customer supplied external phone line and jack.

Contractor shall observe all local and national electrical and building codes.

TAK-4208 TELEPHONE AUTO DIALER UNIT

The Alpha Communications® / Cornell **TAK-4208** is a fully programmable auto dialer and digital announcer, designed for message notification. Once an alarm contact is actuated, the **TAK-4208** can dial up to eight (8) phone numbers and play a pre-recorded message up to one (1) minute in length.

Messages can be recorded locally or remotely. When configured as an alarm dialer, the **TAK-4208** has call progress detection capability with normal and fast busy, call pickup, CPC, and ring-to-answer detection.

Programming can be done with a touch tone phone, or by using a PC with a serial port connection and the supplied software. The **TAK-4208** comes with the required 12VDC plug-in power supply, and has up to eight (8) inputs.

FEATURES

- Easily Installs Right on Finished Wall Surface or in Optional Junction Box
- Operates on Safe Low-Voltage Class II Wiring
- Positive Screw Terminal and Plug-in Connectors
- Works with a variety of alarm notification equipment
- Easily programs with a touch tone phone or PC

SPECIFICATIONS

Dimensions:	Height: 6.30" (161mm) Width: 8.30" (211mm) Depth: 1.80" (46mm) from mounting surface
Construction:	Black painted metal case
Connections:	Positive screw terminal and plug-in connectors
Mounting:	Surface-mounted (usually installed near the other system central equipment).

Alpha Communications

42 Central Drive • Farmingdale • NY • 11735-1202 • Phone: (631) 777-5500 • Fax: (631) 777-5599
TOLL-FREE: (800) 666-4800 • Web: www.alphacommunications.com • Email: info@alphacommunications.com

Copyright© 1998-2023 Alpha Communications® - All Rights Reserved.

Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.