

# Security Intercom System

## Power Supply Cat. 4380



### FEATURES

- Wide range AC input
- Fully enclosed
- Highly regulated output
- Overcurrent protection

### DESCRIPTION

The Cat. 4380 Power Supply is used to furnish 24VDC for up to 24 stations. Multiple power supplies are required for larger systems.

### TECHNICAL DATA

#### Operating Voltage

- 24VDC @ 2.5A

#### Input

##### AC Input Voltage:

- 90 to 264VAC

##### AC Input Frequency:

- 47 to 63Hz

##### AC Input Current:

- 1.7 Arms (115Vac)
- 0.8 Arms (230Vac)

##### AC Surge Immunity:

- EN 61000-4-5, Level 3

#### Output

##### Overvoltage Protection:

- Included, all models

##### Short Circuit Protection:

- Auto Restart

### Environmental

#### Operation Temperature:

- 0 to 40°C

#### Humidity:

- 20 to 95% R.H.  
(Non-condensing)

#### Emissions:

- FCC Class B
- EN 55022B

#### Immunity:

- EN 61000-4-2, Level 2
- EN 61000-4-3, Level 2
- EN 61000-4-4, Level 2

#### Certification

- Listed UL 813
- C-UL C22.2 No. 1-98